

## DISTRICT PLAN TEXT AMENDMENTS

Key:

For the purposes of this plan change, any unchanged text is shown as normal text or in **bold**, any text proposed to be added by the plan change is shown as **bold underlined** and text to be deleted as ~~**bold strikethrough**~~.

Text in red box is a note to readers.

Text in green font identifies existing terms in Chapter 2 – Definitions. Where the proposed change contains a term defined in Chapter 2 – Definitions, the term is shown as **bold underlined text in green** and that to be deleted as ~~**bold strikethrough in green**~~. New definition in a proposed rule is **bold green text underlined in black**.

Text in black/green shaded in grey is a Council Decision subject to appeal.

Text in light blue shaded in grey is a Council Decision proposed to be deleted by this Plan Change.

Text in blue font indicates links to other provisions in the district Plan and/or external documents. These will have pop-ups and links, respectively, in the on-line Christchurch District Plan.

## Chapter 5 Natural Hazards

### 5.1 Introduction

- a. This introduction is to assist the lay reader to understand how this chapter works and what it applies to. It is not an aid to interpretation in a legal sense.
- b. The provisions in this chapter give effect to the [Chapter 3 Strategic Directions Objectives](#).
- c. Natural hazards are defined in the Resource Management Act 1991 as:

*any atmospheric or earth or water related occurrence (including earthquake, tsunami, erosion, volcanic and geothermal activity, landslip, subsidence, sedimentation, wind, drought, fire, or flooding) the action of which adversely affects or may adversely affect human life, property, or other aspects of the environment.*
- d. This chapter identifies the ways in which the impacts from a range of natural hazards are managed, particularly in relation to the use, development and maintenance of land, **buildings** and infrastructure.
- e. Natural hazard risk can arise from:
  - i. intense rainfall events causing flooding from rivers, streams, overland flow and lakes;
  - ii. earthquakes;
  - iii. liquefaction;
  - iv. slope instability, being cliff collapse, rockfall or boulder roll, and mass movement;
  - v. tsunami;
  - vi. inundation from the sea and storm surge;

- vii. coastal erosion;
  - viii. fire;
  - ix. exacerbation of some of the hazards above through climate change and sea level rise; and
  - x. multiple hazards consisting of combinations of the above.
- f. The primary approach to managing natural hazards in this **District Plan** is to take what is called a “risk-based” approach. Such an approach considers various scales of a particular natural hazard event (for example different magnitude earthquakes and different intensities and durations of rainfall events), together with the likelihood of that particular event occurring and the effects that it would cause, particularly on people and property.
- g. In this chapter, risk is expressed in a number of ways. For example, in areas at risk from slope instability such as cliff collapse, rockfall, or mass movement, it is the degree of risk to people’s lives that is of primary concern. In most areas at risk from flooding, the primary concern relates to damage to property and how often this may occur.
- h. In areas of slope instability, risk is expressed as an “**Annual Individual Fatality Risk**” or **AIFR**, being the probability of a fatality for an individual occupying a specific **site** in any one year as a result of slope instability. Calculating this risk involves a number of underlying assumptions, such as the percentage of time an individual is on **site** or in a **residential unit**, the level of seismicity (taking into account that the Canterbury earthquakes are expected to decrease over time) and whether or not people would be evacuated following a major seismic event. Given the range of inputs into **AIFR**, there is an uncertainty in the calculated value of the **AIFR** which can mean there is a higher or lower level of actual risk. Recognising this, and the area-wide scale of the slope instability mapping, a process has been included that allows for rockfall risk to be recalculated on a site-specific basis through an independent risk assessment that has been supported by an independent peer review.
- i. In areas of flooding, the term “**Annual Exceedance Probability**” or **AEP** is used to describe the likelihood of a flooding event of a certain size occurring. This is a different way of expressing the commonly used term “return period” – for example a storm with a return period of 200 years has an **AEP** of 1/200 (i.e. the reciprocal of the return period) or 0.5%, and means there is a 0.5% chance of a storm of that size happening in any one year.
- j. In areas where there is likely to be a liquefaction risk to property, no specific measure of risk is applied. The area mapped is based on whether liquefaction is more likely to occur than not. Within that area, liquefaction risk and appropriate mitigation is assessed on a site-specific basis using best practice geotechnical and engineering methods to determine the performance of infrastructure and **buildings**.
- k. The level of control over activities in the **District Plan** is related to the consequence of the various natural hazards and whether such risks are considered to be acceptable or not. There is also a category in between where, following proper assessment, risk may be able to be managed such that the risk is reduced to acceptable levels.
- l. In locations where the risk from natural hazards is considered to be unacceptable and such risks cannot practically be reduced to acceptable levels, new activities in those areas are generally to be avoided. This includes areas such as Cliff Collapse Management Area 1, Cliff Collapse Management

Area 2 and Rockfall Management Area 1, but also includes adjacent areas where risk cannot be adequately remedied or mitigated.

- m. Where risk from natural hazards is able to be managed to acceptable levels, the Council may require assessment and mitigation in relation to potential effects on development from natural hazards in order to reduce risk to a level that is deemed acceptable in the circumstances. Examples are Rockfall Management Area 2, the Flood Management Area and the Liquefaction Management Area. The planning maps also include Flood Ponding Management Areas which are required for flood storage capacity, thereby reducing impacts of downstream flooding, and the function of these is recognised in the District Plan.
- n. Where risk is considered to be acceptable without any interventions, and is similar to the levels of many everyday risks that people face and accept each day, there is no intervention required by the District Plan.

## 5.2 Objectives and Policies

### 5.2.1 Natural Hazard Objectives

#### 5.2.1.1 Objective — Natural hazards

- a. The Objective for this chapter is Objective 3.3.6 in Chapter 3 Strategic Directions.

### 5.2.2 Natural hazards policies

#### 5.2.2.1 General natural hazards policies

##### 5.2.2.1.1 Policy — Avoid new development where there is unacceptable risk

- a. Avoid new subdivision, use and development, including new urban zonings, where the risk from a natural hazard is assessed as being unacceptable.

##### 5.2.2.1.2 Policy — Manage activities to address natural hazard risks

- a. Manage activities in all areas subject to natural hazards in a manner that is commensurate with the likelihood and consequences of a natural hazard event on life and property.

##### 5.2.2.1.3 Policy — Infrastructure

- a. Avoid locating new critical infrastructure where it is at risk of being significantly affected by a natural hazard unless, considering functional and operational requirements, there is no reasonable alternative location or method.
- b. Enable critical infrastructure to be designed, maintained and managed to function to the extent practicable during and after natural hazard events.

- c. Recognise the benefits of infrastructure and the need for its repair, maintenance and ongoing use in areas affected by natural hazards.

#### **5.2.2.1.4 Policy — No transferring of natural hazard risk**

- a. Ensure that **subdivision**, use and development (including proposals for hazard mitigation works or hazard removal) do not transfer or create unacceptable natural hazard risk to other people, property, infrastructure or the natural environment.

#### **5.2.2.1.5 Policy — Natural features providing hazard resilience**

- a. Protect natural features which assist in avoiding or reducing the risk of natural hazards, such as natural ponding areas, coastal dunes, **wetlands**, **water body** margins and riparian vegetation from inappropriate **subdivision**, use and development and where appropriate restore, maintain or enhance the functioning of these features.

#### **5.2.2.1.6 Policy — Awareness of natural hazards**

- a. Ensure people are informed about the natural hazards relating to their properties and surrounding area, including through provision of relevant information on Land Information Memoranda and hazard mapping on the **Council's** website.
- b. Encourage property owners to incorporate measures into **buildings** including earthquake damaged **buildings** beyond existing use rights or minimum building standards to avoid or mitigate natural hazards affecting their property.

#### **5.2.2.1.7 Policy — Repair of earthquake damaged land**

- a. Facilitate recovery by enabling property owners to make repairs to earthquake damaged land for residential purposes, where these repairs will appropriately manage adverse effects on people, property or the natural environment.
- b. Recognise that the repair of other earthquake damaged land is necessary as part of recovery.

#### **5.2.2.1.8 Policy – Assessment of hazards**

- a. Ensure that the level of assessment undertaken for plan changes, **subdivision** or development reflects the potential scale and significance of the hazard; and the nature and scale of the re-zoning, **subdivision** or development and its susceptibility to those hazards.

### **5.2.2.2 Policy for managing risk from flooding**

#### **5.2.2.2.1 Policy — Flooding**

- a. Map hazard risk for the **Flood Management Area** based on:
  - a modelled 0.5% **AEP** (1 in 200-year) rainfall event plus a 5% **AEP** (1 in 20-year) tide event plus 250mm **freeboard**; OR a modelled 5% **AEP** (1 in 20-year flood event) plus a 0.5% **AEP** (1 in 200-

year) tide event plus 250mm freeboard; OR 11.9m above Christchurch City Council Datum (the maximum 200-year tidal contour) plus 250mm freeboard; whichever is the greater; and

allowance for 1 metre of sea level rise and an increase in rainfall intensity by 16% through to 2115 as a result of climate change; and

a maximum buffer extension of the modelled rainfall event areas by 60 metres in a north/south and east/west direction.

b. In the High Flood Hazard Management Area:

provide for development of a residential unit on residentially zoned land where the flooding risk is predominantly influenced by sea-level rise and where appropriate mitigation can be provided that protects people's safety, well-being and property from unacceptable risk; and

within the Specific Purpose (Ōtākaro Avon River Corridor) Zone, provide for structures in accordance with Policy 13.14.2.1.8.

In all other cases, avoid subdivision, use or development where it will increase the potential risk to people's safety, well-being and property.

- c. Avoid activities locating where they could undermine the integrity of the Waimakariri River primary stopbank system, and restrict activities locating where they could undermine the integrity of the Waimakariri River secondary stopbank system.
- d. Maintain the flood storage capacity and function of natural floodplains, wetlands and ponding areas, including the Hendersons Basin, Cashmere Stream Floodplain, Hoon Hay Valley, Cashmere-Worsleys Ponding Area, Cranford Basin and Lower Styx Ponding Area<sup>1</sup>.
- e. Except for filling required to meet minimum floor levels, ensure that filling in urban areas at risk of flooding in a major flood event does not transfer flooding risk to other people, property, infrastructure or the natural environment.
- f. Reduce potential flood damage by ensuring floor levels for new buildings or additions to buildings, except those unlikely to suffer material damage, are above flooding predicted to occur in a major flood event, including an allowance for appropriate freeboard.

### 5.2.2.3 Policy for managing risk from liquefaction

#### 5.2.2.3.1 Policy — Management of liquefaction risk

- a. Map the Liquefaction Management Area based on a district-wide assessment of where damaging liquefaction is more likely to occur.
- b. Provide for re-zoning, subdivision, use and development on flat land where liquefaction risk has been appropriately identified and assessed, and can be adequately remedied or mitigated.

---

<sup>1</sup> This policy does not foreclose compensatory storage being provided for where filling is required.

**5.2.2.4 Policies for managing risk from slope instability**

**5.2.2.4.1 Policy — Slope instability**

- a. Map areas of slope instability risk at an area-wide scale using the following fixed inputs into calculations<sup>2</sup> that establish the **Annual Individual Fatality Risk (AIFR)** for a typical residential site<sup>3</sup>:

	<b>Slope instability hazard management area</b>	<b>Inputs</b>			<b>Mapped risk (AIFR)</b>
		Percentage of a day the property is assumed to be occupied (%)	Year of predicted seismic activity used in modelling	Whether or not the property is evacuated immediately following a Natural Hazard Event	
i.	Cliff Collapse Management Area 1	100	2012	No	$\geq 10^{-2}$
ii.	Cliff Collapse Management Area 2	100	2012	No	$\geq 10^{-4}$
iii.	Rockfall Management Area 1	67	2016	Yes	$\geq 10^{-4}$
iv.	Rockfall Management Area 2	100	2016	No	$\geq 10^{-4}$
v.	Mass Movement Management Area 1	67	2016	Yes	$\geq 10^{-4}$
vi.	Mass Movement Management Areas 2 & 3	Refer to natural hazard maps			

- b. In slope instability hazard management areas in the Port Hills and across **Banks Peninsula**:  
 avoid **subdivision**, use and development where the activity will result in an unacceptable risk to life safety (**AIFR**  $\geq 10^{-4}$  using the GNS Science method and parameters for establishing life safety

<sup>2</sup> Using the method and parameters described in GNS Science Consultancy Report 2011/311 Canterbury Earthquakes Port Hills Slope Stability: Pilot study for assessing life-safety risk from rockfalls (boulder rolls) and GNS Science Consultancy Reports 2012/57 Canterbury Earthquakes Port Hills Slope Stability: Pilot study for assessing life-safety risk from cliff collapse and 2012/124 Port Hills Slope Stability: Life-safety risk from cliff collapse in the Port Hills, and any subsequent updates to those reports by GNS Science. Calculations also include modelling and estimates, such as probability of a rockfall/cliff collapse event, vulnerability, rock/debris volumes and rockfall run-out. The mapping does not take account of **hazard mitigation works**. Rocks can, and will, fall outside of the mapped hazard risk areas, however the risk of a fatality is lower.

<sup>3</sup> Except Mass Movement Management Areas 2 & 3 which are mapped based on potential effect on property, not **Annual Individual Fatality Risk**.

risk), taking into account all relevant site-specific information and any **hazard mitigation works** proposed; and

otherwise, manage **subdivision**, use and development so that risk of damage to property and infrastructure is mitigated to an acceptable extent.

#### **5.2.2.4.2 Policy — Site-specific risk assessment for AIFR Certificates<sup>4</sup> in certain areas potentially affected by rockfall and/or cliff collapse**

- a. Provide for site-specific assessment of risk from rockfall and/or cliff collapse, in Rockfall Management Area 1, Rockfall Management Area 2, and/or Cliff Collapse Management Area 2, in accordance with the method and parameters described in **Policy 5.2.2.4.1a<sup>5</sup>** (along with all relevant site-specific information) in order to allow for the issue of **AIFR** certificates.
- b. Make information from site-specific assessments of risk from rockfall and/or cliff collapse (which have been certified by the **Council**) readily publicly available.
- c. Regularly notify changes to the **District Plan**, as required to change the planning maps, in order to reflect updated information from site-specific assessments of life-safety risk from rockfall and/or cliff collapse which have been certified by the **Council**.

#### **5.2.2.4.3 Policy — Slope instability for all of the Port Hills and Banks Peninsula**

- a. In areas not already identified in **Policy 5.2.2.4.1a** as being subject to cliff collapse, rockfall or mass movement, but where the land may be subject to slope instability:
  - i. to the extent appropriate, require proposals for **subdivision**, use and development to be assessed by a geotechnical specialist to evaluate the presence of hazards and level of risk to people and property (including infrastructure) from slope instability hazards; and
  - ii. only allow **subdivision**, use and development where risk can be reduced to an acceptable level.
- b. Avoid **hazard mitigation works** in areas of the Port Hills and across **Banks Peninsula** where cliff collapse or mass movement is likely to destroy or significantly damage such works, or where construction or maintenance of **hazard mitigation works** creates a safety hazard, unless reasonably required to protect **critical infrastructure**.
- c. Control **hazard mitigation works** and hazard removal works for slope instability across all other areas of the Port Hills and **Banks Peninsula**, to ensure that works:  
  
are effective;  
  
do not worsen any existing natural hazard; and  
  
do not transfer or increase the risk to other people, property, including **critical infrastructure**, or the natural environment.

**NOTE: The provisions of the Christchurch City Plan and the Banks Peninsula District Plan that relate to coastal hazards continue to apply. The provisions of those plans that still apply (including the 20m building and earthworks setback from mean high water springs) are set out in [this table](#).**

<sup>4</sup> Refer to [Rule 5.6.1.2](#)

<sup>5</sup> This method does not take account of **hazard mitigation works**.

**5.2.2.5.1 Policy – Managing development in Qualifying Matter Coastal Hazard Management Areas**

- a. Within the following Qualifying Matters, development, subdivision and land use that would provide for intensification of any site shall be avoided, unless the risk is from coastal inundation and a site specific assessment demonstrates the risk is low or very low based on thresholds defined in Table 5.2.2.5.1a below:


Coastal Hazard High Risk Management Area;

Coastal Hazard Medium Risk Management Area.

**Table 5.2.2.5.1a thresholds for coastal inundation**

<u>Coastal inundation risk category</u>	<u>Flood depth based on 0.6m of sea level rise (higher certainty)</u>	<u>Flood depths based on 1.2m of sea level rise (less certainty – higher consequence)</u>
<u>Very low</u>	<u>Dry</u>	<u>d &lt; 0.4m</u>
<u>Low</u>	<u>d &lt; 0.4m</u>	<u>0.4m &lt; d &lt; 1.0m</u>
<u>Medium</u>	<u>0.4m &lt; d &lt; 1.0m</u>	<u>d &gt; 1.0m</u>
<u>High</u>	<u>d &gt; 1.0m</u>	<u>d &gt; 1.6m</u>

Note - d represents the depth of coastal flooding in a flood event, which factors in the sea level amount considered i.e. 0.6m of sea level rise does not equate to 0.6m of flooding.



- b. Replacement buildings, accessory buildings and extensions/additions to buildings are enabled where effects are mitigated to an acceptable level based on a site specific assessment, and having regard to the level and timing of the hazard. This could be by use of an appropriate risk based trigger or alternative methods.

### **5.2.2.5.2 Policy – Managing development within Qualifying Matter Tsunami Management Area**

- a. **Within the Tsunami Management Area Qualifying Matter, avoid development, subdivision and land use that would provide for intensification of any site, unless the risk to life and property is acceptable.**

## **5.3 How to interpret and apply the rules**

- a. The rules that apply in the natural hazard overlay areas in the planning maps are listed in:
- i. **Rule 5.4** – Flood hazard:
    - A. **Rule 5.4.1** – Activities and earthworks in the Flood Management Area;
    - B. **Rule 5.4.2** – Activities and earthworks in the Te Waihora/Lake Ellesmere and Wairewa/Lake Forsyth Flood Management Areas;
    - C. **Rule 5.4.3** – Activities and earthworks in the Waimakariri Flood Management Area;
    - D. **Rule 5.4.4** – Repair of land used for residential purposes damaged by earthquakes within the Flood Management Areas in rural and residential zones;
    - E. **Rule 5.4.5** – Activities and earthworks in the Flood Ponding Management Area; and
    - F. **Rule 5.4.6** – Activities in the High Flood Hazard Management Area.
  - ii. **Rule 5.4A – Qualifying Matter Coastal Hazard Management Areas**
  - ~~ii-iii.~~ **Rule 5.5** – Liquefaction hazard; and
  - ~~iii-iv.~~ **Rule 5.6** – Slope instability.
- b. The **Flood Management Areas** have separate, specific provisions in identified geographical areas identified on the planning maps as set out below. **Rule 5.4.1** does not apply to areas subject to **Rules 5.4.2** or **5.4.3**:
- i. **Rule 5.4.1** – Activities and earthworks in the Flood Management Area;
  - ii. **Rule 5.4.2** – Activities and earthworks in the Te Waihora/Lake Ellesmere and Wairewa/Lake Forsyth Flood Management Areas;
  - iii. **Rule 5.4.3** – Activities and earthworks in the Waimakariri Flood Management Area.
- c. The information requirements for resource consent applications are set out in **Rule 5.7**.
- d. The activities covered by the rules in this chapter are also subject to the rules in the relevant zone chapters.
- e. The activity status tables, rules and standards in the following chapters also apply:
- 4** Hazardous Substances and Contaminated Land
  - 6** General Rules and Procedures

- 7 Transport
- 8 Subdivision, Development and Earthworks
- 9 Natural and Cultural Heritage
- 11 Utilities and Energy

**NOTE:** The provisions of the Christchurch City Plan and the Banks Peninsula District Plan that relate to coastal hazards continue to apply. The provisions of those plans that still apply (including the 20m building and earthworks setback from mean high water springs) are set out in [this table](#).

## 5.4 Rules - Flood hazard

- a. Areas identified as being subject to high hazard flooding<sup>6</sup> are identified on the planning maps as **High Flood Hazard Management Area**.
- b. Areas identified as being subject to inundation in a major flooding event are identified as **Flood Management Area**. Within this area, where the required floors levels are certain and already established by the **Council**, they are identified on the planning maps as being within the Fixed Minimum Floor Level Overlay. Where they are not accurately modelled and further modelling is required, the **Council** will, on request, review its current information and issue a Minimum Floor Level Certificate that will certify the floor level necessary for that **site** based on available information.
- c. Areas that are important for stormwater retention are also identified on the planning maps as Flood Ponding Management Area.

### 5.4.1 Activities and earthworks in the Flood Management Area

#### 5.4.1.1 Permitted activities

- a. The activities listed below are permitted activities where the activity is located in the area shown on the planning maps as **Flood Management Area** (other than in a Transport Zone, where the **Flood Management Area** rules do not apply), if they meet the activity specific standards set out in [Table 5.4.1.1b](#).
- b. Activities may also be restricted discretionary as specified in [Rule 5.4.1.5](#).
- c. Exemptions relating to this rule can be found in [Rule 5.4.1.4](#).

<sup>6</sup> High hazard flooding includes areas that flood to a depth greater than 1 metre, or the depth (m) x velocity (ms<sup>-1</sup>) of the over land flow is greater than 1 in a 0.2% **AEP** (1 in 500-year) flood event

- d. For **filling** or **excavation** (before 31 December 2018) for repair of land used for residential purposes and damaged by earthquakes, see [Rule 5.4.4](#).
- e. For the purpose of determining appropriate floor levels for P1 and P2, the following models will be used:

**Table 5.4.1.1a**

	<b>Flood Management Area Catchment</b>	<b>Model</b>	<b>Version</b>
i.	Styx	Styx River Hydrologic and Hydraulic Model	R004
ii.	Avon	Avon River Hydrologic and Hydraulic Model	D13
iii.	Heathcote	Heathcote River Hydrologic and Hydraulic Model	2012 Design
iv.	Sumner	Sumner Floodplain Hydrologic and Hydraulic Model	12N
v.	Avoca Heathcote Valley	Avaco Heathcote Valley Hydrologic and Hydraulic Model	AV-ED2014

**Table 5.4.1.1b**

<b>Activity</b>		<b>Activity specific standards</b>
<b>P1</b>	New <b>buildings</b> located within the Fixed Minimum Floor Level Overlay, unless specified in P5, P6, P7, P8 or P9 in <a href="#">Rule 5.4.1.1</a> .	a. Minimum floor levels shall be the highest of the following: flooding predicted to occur in a 0.5% <b>AEP</b> (1 in 200-year) rainfall event concurrent with a 5% <b>AEP</b> (1 in 20-year) tidal event, including 1metre sea level rise plus 400mm <b>freeboard</b> , as predicted by the relevant <b>Council</b> model and version identified in <a href="#">Table 5.4.1.1a</a> ; or
<b>P2</b>	Additions to existing <b>buildings</b> which increase the <b>ground floor area</b> of the <b>building</b> located within the Fixed Minimum Floor Level Overlay, unless specified in P6, P7, P8 or P9 in <a href="#">Rule 5.4.1.1</a> .	flooding predicted to occur in a 0.5% <b>AEP</b> (1 in 200-year) tidal event concurrent with a 5% (1 in 20-year) rainfall event, including 1m sea level rise plus 400mm <b>freeboard</b> , as predicted by the relevant <b>Council</b> model and version identified in <a href="#">Table 5.4.1.1a</a> ; or  12.3 metres above <b>Christchurch City Council Datum</b> .  <i>(Link to Council's Floor Level Viewer for Fixed Minimum Floor Levels)</i>

Activity		Activity specific standards
<b>P3</b>	New <b>buildings</b> outside the Fixed Minimum Floor Level Overlay unless specified in P5, P6, P7, P8 or P9 in <a href="#">Rule 5.4.1.1</a> .	a. Minimum floor levels shall be the level specified in the Minimum Floor Level Certificate (refer to <a href="#">Rule 5.4.1.2</a> )
<b>P4</b>	Additions to existing <b>buildings</b> which increase the <b>ground floor area</b> of the <b>building</b> outside the Fixed Minimum Floor Level Overlay unless specified in P6, P7, P8 or P9 in <a href="#">Rule 5.4.1.1</a> .	a. Minimum floor levels shall be the level specified in the Minimum Floor Level Certificate (refer to <a href="#">Rule 5.4.1.2</a> )
<b>P5</b>	Additions to existing <b>buildings</b> that do not increase the <b>ground floor area</b> of the <b>building</b> .	Nil
<b>P6</b>	Additions other than <b>garages</b> provided for in <a href="#">Rule 5.4.1.1 P7</a> which do not increase the <b>ground floor area</b> of an existing <b>building</b> by more than 25m <sup>2</sup> within any continuous period of 10 years.	Nil
<b>P7</b>	<b>Garages</b> of 40 m <sup>2</sup> or less in area, and any other <b>accessory buildings</b> without floors.	Nil
<b>P8</b>	Decks, swimming pools, and unenclosed <b>buildings</b> without floors.	Nil
<b>P9</b>	<b>Utilities</b> and <b>LPG</b> storage tanks.	Nil
<b>P10</b>	<b>Filling</b> or <b>excavation</b> for <b>residential building platforms</b> only to the extent necessary to achieve the minimum floor levels specified for P1, P2, P3 and P4 in <a href="#">Rule 5.4.1.1</a> for new <b>buildings</b> and for additions to <b>buildings</b> .	Nil
<b>P11</b>	<b>Filling</b> or <b>excavation</b> associated with the maintenance of flood protection and bank erosion protection works; and the maintenance of existing drains or ponds.	Nil
<b>P12</b>	<b>Filling</b> or <b>excavation</b> associated with <b>utilities</b> , or the replacement, repair or maintenance of existing <b>utilities</b> .	Nil

Activity		Activity specific standards
<b>P13</b>	<b>Filling</b> or <b>excavation</b> in zones other than commercial, industrial and rural zones that is not provided for under <a href="#">Rule 5.4.1.1</a> P10-P12 or P17-P18.	<p>a. A maximum height of 0.3m of <b>filling</b> above <b>ground level</b> and 0.6m depth of <b>excavation</b> below <b>ground level</b>; and</p> <p>b. A maximum volume of <b>filling</b> above <b>ground level</b> of 10m<sup>3</sup> per <b>site</b>, and a maximum cumulative volume of <b>filling</b> and <b>excavation</b> of 25m<sup>3</sup> per <b>site</b>, in each case within any continuous period of 10 years.</p> <p>Or</p> <p>c. The <b>excavation</b> and <b>filling</b> is associated with the maintenance and/or replacement of underground petroleum storage systems and where, following reinstatement of the underground petroleum storage systems, the <b>site</b> will have a finished contour that is equivalent to the <b>ground level</b> at the commencement of the works.</p>
<b>P14</b>	<b>Filling</b> or <b>excavation</b> in commercial and industrial zones that is not provided for under <a href="#">Rule 5.4.1.1</a> P10-P12 or P17.	<p>a. A maximum height of 0.3m of <b>filling</b> above <b>ground level</b> and 0.6 metres depth of <b>excavation</b> below <b>ground level</b>; and</p> <p>b. A maximum volume of <b>filling</b> above <b>ground level</b> of 20m<sup>3</sup> per <b>site</b>, and a maximum cumulative volume of <b>filling</b> and <b>excavation</b> of 50m<sup>3</sup> per <b>site</b>, in each case within any continuous period of 10 years.</p> <p>Or</p> <p>c. The <b>excavation</b> and <b>filling</b> is associated with the maintenance and/or replacement of underground petroleum storage systems and where, following reinstatement of the underground petroleum storage systems, the <b>site</b> will have a finished contour that is equivalent to the <b>ground level</b> at the commencement of the works.</p>
<b>P15</b>	<b>Filling</b> or <b>excavation</b> in rural zones that is not provided for under <a href="#">Rule 5.4.1.1</a> P10-P12 or P17.	<p>a. A maximum height of 0.2m of <b>filling</b> above <b>ground level</b> and 0.6 metres depth of <b>excavation</b> below <b>ground level</b>; and</p> <p>b. A maximum volume of <b>filling</b> above <b>ground level</b> of 100m<sup>3</sup> per <b>site</b> within any continuous period of 10 years.</p> <p>Or</p>

Activity		Activity specific standards
		c. The <b>excavation</b> and <b>filling</b> is associated with the maintenance and/or replacement of underground petroleum storage systems and where, following reinstatement of the underground petroleum storage systems, the <b>site</b> will have a finished contour that is equivalent to the <b>ground level</b> at the commencement of the works.
<b>P16</b>	Outdoor storage of transiting shipping containers in commercial and industrial zones.	Nil
<b>P17</b>	<b>Excavation</b> and <b>filling</b> within the area identified in <a href="#">Appendix 8.10.76d</a> - Cashmere/Worsleys Development Plan.	<p>a. The <b>excavation</b> and <b>filling</b> will not result in the reduction in the existing potential storage volume of water that is able to be retained within the development plan area, prior to any residential zone development, in a 0.2% <b>AEP</b> event up to the existing Worsleys Road minimum centreline level of 18.89 metres (<b>Christchurch City Council Datum</b>). The design shall also accommodate additional storage for any additional stormwater that could be discharged from the development of the residential zones and <b>roads</b> in a 0.2% <b>AEP</b> event.</p> <p>b. All <b>roads</b> are filled so that the crown of the <b>road</b> is no lower than <b>RL 18.7 metres (Christchurch City Council Datum)</b>, except for the realigned Worsleys Road required in the Development Plan. The crown of Worsleys Road shall be no lower than <b>RL 18.89 metres (Christchurch City Council Datum)</b>.</p> <p>c. The side slopes of all areas filled or excavated in accordance with a. and b. above shall not exceed an angle of 1 in 5.</p>
<b>P18</b>	<b>Filling</b> or <b>excavation</b> in the Specific Purpose (Ōtākaro Avon River Corridor) Zone that is not provided for under <a href="#">Rule 5.4.1.1</a> P10-P12	<p>a. A maximum height of 0.3m of <b>filling</b> above <b>ground level</b> and 0.6m depth of <b>excavation</b> below <b>ground level</b>; and</p> <p>b. A maximum volume of <b>filling</b> above <b>ground level</b> of 20m<sub>3</sub> per <b>site</b> and a maximum cumulative volume of <b>filling</b> and <b>excavation</b> of 50m<sub>3</sub> per hectare, which shall be applied as a ratio in each case within any continuous period of 10 years.</p>

### 5.4.1.2 Minimum floor level certificate

- a. For P3 and P4 in [Table 5.4.1.1b](#), new **buildings** or additions to existing **buildings** within the **Flood Management Area**, but outside of the Fixed Minimum Floor Level Overlay shall have a floor level that is greater than or equal to that specified in a Minimum Floor Level Certificate. The **Council** will issue a Minimum Floor Level Certificate (which will be valid for 2 years from the date of issue) which specifies the design floor level for a **building** calculated as the highest of the following:
  - i. flooding predicted to occur in a 0.5% **AEP** (1 in 200-year) rainfall event concurrent with a 5% **AEP** (1 in 20-year) tidal event, including 1m sea level rise plus 400mm **freeboard**, as predicted by the most up to date **Council** model and any relevant field information; or
  - ii. flooding predicted to occur in a 0.5% **AEP** (1 in 200-year) tidal event concurrent with a 5% **AEP** (1 in 20-year) rainfall event, including 1m sea level rise plus 400mm **freeboard**, as predicted by the most up to date **Council** model and any relevant field information; or
  - iii. 12.3 metres above **Christchurch City Council Datum**.

### 5.4.1.3 Exemptions for daylight recession planes in the Flood Management Area

- a. For P1 and P2 in [Rule 5.4.1.1](#), the applicable daylight recession plane in residential zones (**other than in the Medium Density Residential Zone and High Density Residential Zone**) shall be determined as if the **ground level** at the relevant **boundary** was the minimum floor level set in the activity specific standards in [Rule 5.4.1.1](#), or natural **ground level**, whichever is higher.
- b. For P3 and P4 in [Rule 5.4.1.1](#), the applicable daylight recession plane in residential zones (**other than in the Medium Density Residential Zone and High Density Residential Zone**) shall be determined as if the **ground level** at the relevant **boundary** was the minimum floor level specified in the Minimum Floor Level Certificate issued under [Rule 5.4.1.2](#), or natural **ground level**, whichever is higher.
- c. For the purposes of a. and b. above, the applicable daylight recession plane in residential zones are:
  - i. **Rule 14.4.2.6 Daylight recession planes - Residential Suburban Zone and Residential Suburban Density Transition Zone;**
  - ~~ii. Rule 14.5.2.6 Daylight recession planes - Residential Medium Density Zone;~~
  - ~~iii. ii. Rule 14.8.2.5 Daylight recession planes – Residential Banks Peninsula Zone;~~
  - ~~iv. iii. Rule 14.7.2.4 Daylight recession planes – Residential Hills Zone;~~
  - ~~v. iv. Rule 14.9.2.4 Daylight recession planes – Residential Large Lot Zone;~~
  - ~~vi. v. Rule 14.10.2.4 Daylight recession planes – Residential Small Settlement Zone;~~
  - ~~vii. vi. Rule 14.12.2.4 Daylight recession planes - Residential New Neighbourhood Zone Future Urban Zone;-and~~
  - ~~viii. Rule 14.11.2.6 Daylight recession planes – Residential Guest Visitor Accommodation Zone;~~
  - ix. **Rule 14.13.3.2 Daylight recession planes - Enhanced development mechanism;**
  - ~~x. Rule 14.14.2.2 Daylight recession planes – Community housing redevelopment mechanism;~~  
**and**

~~xi. Rule 14.6.2.2 Daylight recession planes – Residential Central City Zone.~~

(Plan Change 4 Council Decision subject to appeal)

#### 5.4.1.4 Exemption for buildings in certain circumstances where a PIM has been issued

- a. Replacement of earthquake-damaged buildings (including partial replacement) in the Flood Management Area are exempt from compliance with the requirements of P1-P4 in Rule 5.4.1.1, provided that:
  - i. for Flood Management Areas made operative on 7 June 2016 or [insert Stage 3 operative date], on or before the date at which those Flood Management Areas became operative, the Council has received an application for a Project Information Memorandum (PIM) for a building on a specific site; AND
  - ii. in response to that application, the Council has issued a PIM that confirms the minimum floor level for the building on that site.

The PIM may be issued before or after the date at which the relevant Flood Management Area became operative, but shall be based on the requirements of the relevant district plan that was operative on the date the PIM was received, or if no rules were relevant under that plan, the New Zealand Building Code as at the date that the application was received.

- b. The exemption to Rule 5.4.1.1 outlined in a. above will cease to apply if construction of the building is not commenced by 30 April 2018.

#### 5.4.1.5 Restricted discretionary activities

- a. The activities listed below are restricted discretionary activities where the activity is located in an area shown on the planning maps as a Flood Management Area.
- b. Discretion to grant or decline consent and impose conditions is restricted to the matters of discretion as set out in the following table.

Table 5.4.1.5a

Activity		The Council's discretion shall be limited to the following matters:
<b>RD1</b>	<ul style="list-style-type: none"> <li>a. New buildings or additions to buildings which are not permitted by the activity status rules and/or activity specific standards for P1 – P9 set out in Rule 5.4.1.1.</li> <li>b. Any application arising from this rule shall not</li> </ul>	<ul style="list-style-type: none"> <li>a. The Council's discretion is limited to the following matters:                             <ul style="list-style-type: none"> <li>setting of minimum floor levels</li> <li>mitigation of the effects of flooding</li> </ul> </li> <li>b. These restricted discretionary activities will be assessed against the following criteria:                             <ul style="list-style-type: none"> <li>The frequency at which any proposed building or addition is predicted to be flooded and the extent</li> </ul> </li> </ul>

Activity	The Council's discretion shall be limited to the following matters:	
	be limited or publicly notified.	<p>of damage likely to occur in such an event.</p> <p>Whether any mitigation measures are proposed, their effectiveness and environmental effects, and any benefits to the wider area associated with flood management.</p> <p>Whether there are any positive effects from the reduction in floor levels in relation to neighbouring buildings or streetscape.</p>
RD2	<p>Filling or excavation which is not a permitted activity under P10, P11, P12, or P17 set out in Rule 5.4.1.1, or filling or excavation that exceeds the standards in P13 - P15 or P18 set out in Rule 5.4.1.1.</p>	<p>a. The Council's discretion is limited to the following matters:</p> <p>timing, location, scale and nature of earthworks; earthworks method; and</p> <p>mitigation of effects as they impact flooding and surface drainage</p> <p>b. These restricted discretionary activities will be assessed against the following criteria:</p> <p>Whether any effects arise from filling or excavation on land stability, flooding, water bodies, groundwater and natural ground levels on- and/or off-site, including:</p> <ul style="list-style-type: none"> <li>any likelihood of exacerbation of flooding, erosion, or siltation either upstream or downstream of the site;</li> <li>any likelihood of affecting the stability of adjoining land, including its susceptibility to subsidence or erosion;</li> <li>any adverse effects on other properties from disturbances to surface drainage patterns;</li> <li>effects on flood storage capacity and function in the immediate area, and any wider effects on the flood storage in the catchment including any compensatory storage proposed; and any effects on existing stormwater and flood protection works;</li> <li>any implications for groundwater and the water table, on- or off-site; and</li> <li>any benefits associated with flood management.</li> </ul>

Activity	The Council's discretion shall be limited to the following matters:
	<p>Whether there are any benefits arising that enable the reasonable use of the site.</p> <p>Whether any mitigation measures are proposed, their effectiveness and whether, and to what extent there is a transfer of adverse effects to other properties.</p>

## 5.4.2 Activities and earthworks in the Te Waihora/Lake Ellesmere and Wairewa/Lake Forsyth Flood Management Areas

### 5.4.2.1 Permitted activities

- a. The activities listed below are permitted activities where the activity is located within the areas shown on the planning maps as Te Waihora/Lake Ellesmere or Wairewa/Lake Forsyth Flood Management Areas (other than in a Transport Zone, where the Flood Management Area rules do not apply), if they meet the activity specific standards set out in this table.
- b. Activities may also be restricted discretionary as set out in Rule 5.4.2.4.
- c. For filling or excavation (before 31 December 2018) for repair of land used for residential purposes and damaged by earthquakes, see Rule 5.4.4.

Activity		Activity specific standards
P1	New buildings and additions to existing buildings unless specified in Rule 5.4.2.1 P2-P6.	a. Minimum floor levels shall be the level specified in the Minimum Floor Level Certificate (refer to Rule 5.4.2.2).
P2	Additions to existing buildings that do not increase the ground floor area of the building.	Nil
P3	Additions, other than garages provided for in Rule 5.4.2.1 P4, which do not increase the ground floor area of an existing building by more than 25m <sup>2</sup> within any continuous period of 10 years.	
P4	Garages of 40m <sup>2</sup> or less in area, accessory buildings which are no more than 200m <sup>2</sup> in area, and other accessory buildings without floors.	
P5	Decks, swimming pools, and unenclosed buildings without floors.	
P6	Utilities and LPG storage tanks.	

Activity		Activity specific standards
<b>P7</b>	Filling or excavation for residential building platforms only to the extent necessary to achieve the minimum floor levels specified for P1 in Rule 5.4.2.1 for new buildings and for additions to buildings.	
<b>P8</b>	Filling or excavation associated with the maintenance of flood protection and bank erosion protection works; and the maintenance of existing drains or ponds.	
<b>P9</b>	Filling or excavation associated with utilities, or the replacement, repair or maintenance of existing utilities.	
<b>P10</b>	Filling or excavation that is not provided for under Rule 5.4.2.1 P7-P9 or P11.	<p>a. A maximum height of 0.3 metres of filling above ground level and 0.6 metres depth of excavation below ground level; and</p> <p>b. A maximum volume of filling above ground level of 20m<sup>3</sup> per site, and a maximum cumulative volume of filling and excavation of 50m<sup>3</sup> per site, in each case within any continuous period of 10 years.</p> <p>Or</p> <p>c. The excavation and filling is associated with the maintenance and/or replacement of underground petroleum storage systems and where, following reinstatement of the underground petroleum storage systems, the site will have a finished contour that is equivalent to the ground level at the commencement of the works.</p>
<b>P11</b>	Filling or excavation for the maintenance or upgrading of existing roads on legal road.	a. The works shall not impede the flow of surface water.

### 5.4.2.2 Minimum floor level

- a. For Rule 5.4.2.1 P1, new buildings or additions to existing buildings within the Te Waihora/Lake Ellesmere and Wairewa/Lake Forsyth Flood Management Areas shall have a floor level that is greater than or equal to that specified in a Minimum Floor Level Certificate. The Council will issue a Minimum Floor Level Certificate (which will be valid for 2 years from the date of issue) which specifies the design floor level for a building calculated as the highest of the following:

- i. flooding predicted to occur in a 0.5% AEP (1 in 200-year) rainfall event concurrent with a 5% AEP (1 in 20-year) tidal event, including 1m sea level rise plus 400mm freeboard, as predicted by the most up to date Council approved model and any relevant field information; or
- ii. flooding predicted to occur in a 0.5% AEP (1 in 200-year) tidal event concurrent with a 5% AEP (1 in 20-year) rainfall event, including 1m sea level rise plus 400mm freeboard, as predicted by the most up to date Council approved model and any relevant field information; or
- iii. 12.3 metres above Christchurch City Council Datum.

### 5.4.2.3 Exemptions for daylight recession planes in the Te Waihora/Lake Ellesmere and Wairewa/Lake Forsyth Flood Management Areas

- a. For Rule 5.4.2.1 P1, the applicable daylight recession plane in residential zones shall be determined as if the ground level at the relevant boundary was the minimum floor level specified in the Minimum Floor Level Certificate issued under Rule 5.4.2.2, or natural ground level, whichever is higher.
- b. For the purposes of a. above, the applicable daylight recession plane in residential zones is:
  - i. Rule 14.10.2.4 Daylight recession planes - Residential Small Settlement Zone

#### Advice note:

- 1. For filling or excavation (before 31 December 2018) for repair of land used for residential purposes and damaged by earthquakes, see Rule 5.4.4.

### 5.4.2.4 Restricted discretionary activities

- a. The activities listed below are restricted discretionary activities where the activity is located within the areas shown on the planning maps as Te Waihora/Lake Ellesmere or Wairewa/Lake Forsyth Flood Management Areas.
- b. Discretion to grant or decline consent and impose conditions is restricted to the matters of discretion as set out in the following table.

Activity		The Council's discretion shall be limited to the following matters:
<b>RD1</b>	<ul style="list-style-type: none"> <li>a. New buildings or additions to buildings which are not permitted by the activity status rules and/or activity specific standards for P1 – P6 set out in Rule 5.4.2.1.</li> <li>b. Any application arising from this rule shall not be limited or publicly notified.</li> </ul>	<ul style="list-style-type: none"> <li>a. The Council's discretion is limited to the following matters:               <ul style="list-style-type: none"> <li>i. setting of minimum floor levels; and</li> <li>ii. mitigation of the effects of flooding.</li> </ul> </li> <li>b. These restricted discretionary activities will be assessed against the following criteria:               <ul style="list-style-type: none"> <li>i. The frequency at which any proposed building or addition is predicted to be flooded and the extent of damage likely to occur in such an</li> </ul> </li> </ul>

		<p>event.</p> <p>ii. Whether any mitigation measures are proposed, their effectiveness and environmental effects, and any benefits to the wider area associated with flood management.</p> <p>iii. Whether there are any positive effects from the reduction in floor levels in relation to neighbouring buildings or streetscape.</p>
<p><b>RD2</b></p>	<p>A. Filling or excavation which is not a permitted activity under P7–P9 or P11 set out in Rule 5.4.2.1, or filling or excavation that does not meet the standards in P10 set out in Rule 5.4.2.1.</p>	<p>a. The Council’s discretion is limited to the following matters:</p> <ul style="list-style-type: none"> <li>i. Timing, location, scale and nature of earthworks</li> <li>ii. Earthworks method</li> <li>iii. Mitigation of effects as they impact flooding and surface drainage</li> </ul> <p>b. These restricted discretionary activities will be assessed against the following criteria:</p> <ul style="list-style-type: none"> <li>i. Whether any effects arise from filling or excavation on land stability, flooding, water bodies, groundwater and natural ground levels on- and/or off-site, including: <ul style="list-style-type: none"> <li>A. any likelihood of exacerbation of flooding, erosion, or siltation either upstream or downstream of the site.</li> <li>B. any likelihood of affecting the stability of adjoining land, including its susceptibility to subsidence or erosion.</li> <li>C. any adverse effects on other properties from disturbances to surface drainage patterns.</li> <li>D. effects on flood storage capacity and function in the immediate area, and any wider effects on the flood storage in the catchment including any compensatory storage proposed; and any effects on existing stormwater and flood protection works.</li> <li>E. any implications for groundwater and the water table, on- or off-site.</li> <li>F. any benefits associated with flood management.</li> </ul> </li> <li>ii. Whether there are any benefits arising that enable the reasonable use of the site.</li> </ul>

		<p>iii. Whether any mitigation measures are proposed, their effectiveness and whether, and to what extent there is a transfer of adverse effects to other properties.</p> <p>iv. Whether any effects arise with regard to access, character, ecology and amenity, including:</p> <p>A. any adverse effects or benefits for public access, natural character or ecology of <b>water bodies</b> and <b>wetland</b> areas.</p> <p>B. any adverse effects on <b>amenity values</b> including dust nuisance, visual impact, noise, vibration and traffic associated with the <b>filling</b> or <b>excavation</b>.</p>
--	--	--

### 5.4.3 Activities and earthworks in the Waimakariri Flood Management Area

#### 5.4.3.1 Permitted activities

- a. The activities listed below are permitted activities where the activity is located within the area shown on the planning maps as the Waimakariri **Flood Management Area** (other than in a Transport Zone, where the **Flood Management Area** rules do not apply), if they meet the activity specific standards set out in this table.
- b. Activities may also be restricted discretionary or non-complying as specified in [Rules 5.4.3.3](#) and [5.4.3.4](#).
- c. For **filling** or **excavation** (before 31 December 2018) for repair of land used for residential purposes and damaged by earthquakes, see [Rule 5.4.4](#).

Activity		Activity specific standards
<b>P1</b>	Additions to existing <b>buildings</b> that do not increase the <b>ground floor area</b> of the <b>building</b> .	Nil
<b>P2</b>	Additions other than <b>garages</b> provided for in P3 which do not increase the <b>ground floor area</b> of an existing <b>building</b> by more than 25m <sup>2</sup> within any continuous period of 10 years.	
<b>P3</b>	<b>Garages</b> and any other <b>accessory buildings</b> without floors.	a. The maximum area of any <b>garage</b> or other <b>accessory building</b> shall be no greater than 200m <sup>2</sup> in rural zones and open space zones.

Activity		Activity specific standards
P4	Decks, swimming pools and unenclosed buildings without floors.	Nil
P5	Filling or excavation associated with the maintenance of flood protection and bank erosion protection works; and the maintenance of existing drains or ponds.	
P6	Filling or excavation associated with utilities, or the replacement, repair or maintenance of existing utilities.	
P7	Filling or excavation for post holes for fences and shade cloth structures and tunnel houses, planting holes, and excavation for approved wells.	
P8	Filling or excavation for the maintenance of existing farm tracks and farm yards, or the establishment of new farm tracks and farm yards.	a. The finished ground level shall be maintained to within 200mm of the natural ground level.
P9	<p>a. Application of fertiliser, lime or other plant growth enhancers such as topsoil, bark and trace elements.</p> <p>Advice Note:</p> <p>1. Consent may be required from Canterbury Regional Council, pursuant to section 15 of the Resource Management Act 1991, for the discharge of plant growth enhancers, including fertiliser, into or onto land.</p>	a. For top soil, the maximum volume of filling shall be 100m <sup>3</sup> per site within any continuous period of 10 years.
P10	Filling or excavation for the purposes of establishing and maintaining access ways to a residential unit.	<p>a. Finished ground level shall be maintained to within 200mm of the natural ground level, and</p> <p>b. Access ways shall be constructed so as not to impede the flow of surface water.</p>
P11	Filling for the purposes of landscaping around a residential unit in association with domestic gardening.	a. The maximum volume of filling shall be 10m <sup>3</sup> per site, in each case within any continuous period of 10 years.
P12	Filling or excavation for the maintenance or upgrade of existing roads on legal road.	a. The works shall not impede the flow of surface water.

Activity		Activity specific standards
<b>P13</b>	Filling that is not provided for under Rule 5.4.3.1 P5-P12.	<ul style="list-style-type: none"> <li>a. Either the maximum depth of filling shall be 200mm; and</li> <li>b. The maximum volume of filling shall be 100m<sup>3</sup> per site; and</li> <li>c. The filling shall not impede the flow of surface water; or</li> <li>d. The filling has been approved as part of a building consent.</li> </ul>
<b>P14</b>	Excavation for farm purposes that is not provided for under Rule 5.4.3.1 P5-P12.	<ul style="list-style-type: none"> <li>a. The excavated area is subsequently filled within the following year so that there is no net effect on flood storage.</li> </ul>
<b>P15</b>	New buildings unless specified in P1, P2, P3 or P4 in Rule 5.4.3.1 or RD1 or RD2 in Rule 5.4.3.3 or NC1 or NC2 in Rule 5.4.3.4.	<ul style="list-style-type: none"> <li>a. Minimum floor levels shall be the level specified in the Minimum Floor Level Certificate (refer to Rule 5.4.3.2).</li> </ul>
<b>P16</b>	Additions to existing buildings which increase the ground floor area of the building unless specified in P2, P3 or P4 in Rule 5.4.3.1 or RD1 or RD2 in Rule 5.4.3.3 or NC1 or NC2 in Rule 5.4.3.4.	<ul style="list-style-type: none"> <li>a. Minimum floor levels shall be the level specified in the Minimum Floor Level Certificate (refer to Rule 5.4.3.2).</li> </ul>
<b>P17</b>	Utilities	Nil

### 5.4.3.2 Minimum floor level certificate

- a. For P15 and P16 in Rule 5.4.3.1, new buildings or additions to existing buildings within the Waimakariri Flood Management Area shall have a floor level that is greater than or equal to that specified in a Minimum Floor Level Certificate. The Council will issue a Minimum Floor Level Certificate (which will be valid for 2 years from the date of issue) which specifies the design floor level for a building calculated as the highest of the following:
  - i. flooding predicted to occur in a 0.5% AEP (1 in 200-year) rainfall event concurrent with a 5% AEP (1 in 20-year) tidal event, including 1m sea level rise plus 400mm freeboard, as predicted by the most up to date Council approved model and any relevant field information; or
  - ii. flooding predicted to occur in a 0.5% AEP (1 in 200-year) tidal event concurrent with a 5% AEP (1 in 20-year) rainfall event, including 1m sea level rise plus 400mm freeboard, as predicted by the most up to date Council approved model and any relevant field information; or
  - iii. 12.3 metres above Christchurch City Council Datum.

### 5.4.3.3 Restricted discretionary activities

- a. The activities listed below are restricted discretionary activities where the activity is located within the area shown on the planning maps as the Waimakariri Flood Management Area.
- b. Discretion to grant or decline consent and impose conditions is restricted to the matters of discretion as set out in the following table.

Activity		The Council's discretion shall be limited to the following matters:
RD1	New buildings not located within the 100 metre wide Primary Stopbank Setback as shown on the planning maps and which are not permitted by the activity status rules and/or activity specific standards for P1, P2, P3 or P4 set out in Rule 5.4.3.1.	<ol style="list-style-type: none"> <li>a. The likely effects of proposed filling, excavation and/or building on the functioning of the Waimakariri River stopbank floodplain during and after flood events, including any likelihood of work undertaken exacerbating inundation, erosion, alluvion or avulsion whether upstream or downstream of the site.</li> <li>b. The frequency at which the building or addition is predicted to be inundated by floodwaters and the extent of damage that is likely to occur in such an event.</li> </ol>
RD2	<p>New buildings or new accessory buildings or additions to any accessory building not located within the 50 metre wide Secondary Stopbank Setback as shown on the planning maps and not permitted by the activity status rules and/or activity specific standards for P1, P2, P3 or P4 set out in Rule 5.4.3.1.</p> <p>Any application arising from this rule shall not be limited or publicly notified.</p>	<ol style="list-style-type: none"> <li>c. Whether the floor level of any new building/building addition is above the predicted 0.5% Annual Exceedance Probability (AEP) or 1 in 200 year flood event level with a stopbank breach plus an allowance for freeboard not exceeding 400mm.</li> <li>d. Whether the integrity and/or function of either the primary or secondary stopbanks will be adversely affected by the method to achieve the floor level set out in c.</li> <li>e. Where relevant, any adverse effects likely on land as a result of tidal influences during flood periods including the potential for exacerbation of those effects with potential sea level rise.</li> </ol>
RD3	Filling or excavation within 50 metres of the Secondary Stopbank as shown on the planning maps unless permitted by Rule 5.4.3.1 P10.	<ol style="list-style-type: none"> <li>f. The way in which any building is sited and constructed and its intended use.</li> <li>g. Any adverse effects on access for maintenance of flood protection works.</li> <li>h. The effectiveness and environmental impact of any measures that may be proposed to mitigate the effects of filling, excavation or building.</li> <li>i. The extent to which other properties will be adversely affected as a result of disturbances to surface drainage patterns.</li> <li>j. Any benefits associated with flood management, including the provision of public access, or the</li> </ol>

Activity		The Council's discretion shall be limited to the following matters:
		<p>enhancement of the natural qualities, amenity values or ecology of water bodies and wetlands.</p> <p>k. The extent to which development could result in surface water ponding in the event of flooding, and hence and increased risk of birdstrike.</p> <p>l. Any actual or potential effects on the structural integrity of either the primary or secondary stopbanks including those resulting from scour and backwash from increased water in excavated areas during a flood.</p>
<b>RD4</b>	<p>a. New buildings or additions to buildings which are not permitted by the activity status rules and/or activity specific standards for P1 – P4 or P15 - P17 set out in Rule 5.4.3.1.</p> <p>b. Any application arising from this rule shall not be limited or publicly notified.</p>	<p>a. The Council's discretion is limited to the following matters:</p> <ul style="list-style-type: none"> <li>i. setting of minimum floor levels</li> <li>ii. mitigation of the effects of flooding</li> </ul> <p>b. These restricted discretionary activities will be assessed against the following criteria:</p> <ul style="list-style-type: none"> <li>i. The frequency at which any proposed building or addition is predicted to be flooded and the extent of damage likely to occur in such an event.</li> <li>ii. Whether any mitigation measures are proposed, their effectiveness and environmental effects, and any benefits to the wider area associated with flood management.</li> <li>iii. Whether there are any positive effects from the reduction in floor levels in relation to neighbouring buildings or streetscape.</li> </ul>
<b>RD5</b>	<p>Filling or excavation which is not a permitted activity under P5-P7 set out in Rule 5.4.3.1, or filling or excavation that does not meet the standards in P8-P14 set out in Rule 5.4.3.1.</p>	<p>a. The Council's discretion is limited to the following matters:</p> <ul style="list-style-type: none"> <li>i. timing, location, scale and nature of earthworks;</li> <li>ii. earthworks method; and</li> <li>iii. mitigation of effects as they impact flooding and surface drainage.</li> </ul> <p>b. These restricted discretionary activities will be assessed against the following criteria:</p> <ul style="list-style-type: none"> <li>i. Whether any effects arise from filling or excavation on land stability, flooding, waterways, groundwater and natural ground levels on- and/or off-site, including: <ul style="list-style-type: none"> <li>A. any likelihood of exacerbation of flooding,</li> </ul> </li> </ul>

Activity	The Council's discretion shall be limited to the following matters:
	<p>erosion, or siltation either upstream or downstream of the <b>site</b>;</p> <p>B. any likelihood of affecting the stability of <b>adjoining</b> land, including its susceptibility to subsidence or erosion;</p> <p>C. any adverse effects on other properties from disturbances to surface drainage patterns;</p> <p>D. effects on flood storage capacity and function in the immediate area, and any wider effects on the flood storage in the catchment including any compensatory storage proposed; and any effects on existing stormwater and flood protection works;</p> <p>E. any implications for groundwater and the water table, on- or off-site; and</p> <p>F. any benefits associated with flood management.</p> <p>ii. Whether there are any benefits arising that enable the reasonable use of the <b>site</b>.</p> <p>iii. Whether any mitigation measures are proposed, their effectiveness and whether, and to what extent there is a transfer of adverse effects to other properties.</p> <p>iv. Whether any effects arise with regard to access, character, ecology and amenity, including:</p> <p>A. any adverse effects or benefits for public access, natural character or ecology of <b>water bodies</b> and <b>wetlands</b>; and</p> <p>B. any adverse effects on <b>amenity values</b> including dust nuisance, visual impact, noise, vibration and traffic associated with the <b>filling</b> or <b>excavation</b>.</p>

#### 5.4.3.4 Non-complying activities

- a. The activities listed below are non-complying activities where the activity is located within the area shown on the planning maps as Waimakariri **Flood Management Area**.

Activity

<b>NC1</b>	New <b>buildings</b> or <b>accessory buildings</b> or additions to existing <b>buildings</b> or <b>accessory buildings</b> located within the 100 metre wide Primary Stopbank Setback shown on the planning maps.
<b>NC2</b>	New <b>buildings</b> or new <b>accessory buildings</b> or additions to any existing <b>building</b> or existing <b>accessory building</b> located within the 50 metre wide Secondary Stopbank Setback shown on the planning maps.
<b>NC3</b>	<b>Filling</b> or <b>excavation</b> within the 100 metre wide Primary Stopbank Setback shown on the planning maps.

#### 5.4.3.5 Exemptions to Rules 5.4.3.1, 5.4.3.3 and 5.4.3.4

- a. The following are exemptions from [Rules 5.4.3.1, 5.4.3.3 and 5.4.3.4](#):
  - i. activities within the Clearwater Golf Resort, because [Rule 13.9.4.3.2 Flood Protection – Ground levels at Clearwater Golf Resort](#), within the [Specific Purpose \(Golf Resort\) Zone](#), makes provision for **ground levels** and **building** floor levels; and
  - ii. activities within the Rural Quarry Zone (McLeans Island area) provided for in [Rules 17.8.1, 17.8.2 and 17.8.3](#), provided that no **excavation** shall cut below a surface with a gradient of 3 (horizontal) to 1 (vertical) measure from a point commencing 10 metres from the toe of any existing or consented stopbank (see [Appendix 5.8.1 Gradient for excavation near stopbank for Rule 5.4.3.5.a.ii.](#)).

#### 5.4.4 Repair of land used for residential purposes damaged by earthquakes within Flood Management Areas in rural and residential zones

##### 5.4.4.1 Permitted activities

- a. The activities listed below are permitted activities in the area shown on the planning maps as **Flood Management Area** (including the Te Waihora/Lake Ellesmere and Wairewa/Lake Forsyth **Flood Management Areas**) provided the activity:
  - i. meets all of the activity status rules and activity specific standards in [Rule 5.4.4.1](#); and
  - ii. occurs in a rural or residential zone (except for the Residential Suburban Zone on the corner of Hendersons and Sparks Road); and
  - iii. is commenced prior to the expiry date of this rule on 31 December 2018.
- b. Activities may also be restricted discretionary as specified in [Rule 5.4.4.2](#).
- c. Exemptions from the permitted activity standards are listed in [Rule 5.4.4.3](#).

**Table 5.4.4.1a**

Activity	Activity specific standards
<p><b>P1</b></p>	<p>Any <b>filling</b> or <b>excavation</b> activity undertaken to repair land used for residential purposes and damaged by the earthquakes, where any <b>site</b> or part of a <b>site</b> is located within a <b>Flood Management Area</b> unless specified by P2 in <b>Rule 5.4.4.1</b>.</p>
<p><b>P2</b></p>	<p>a. Any <b>filling</b>, <b>excavation</b> or <b>disturbance of soil</b> shall not exceed the standards in <b>Tables 5.4.4.1b</b> or <b>5.4.4.1c</b> (whichever applies) under <b>Rule 5.4.4.1</b>.</p> <p>b. There shall be no <b>filling</b>, <b>excavation</b> or <b>disturbance of soil</b> within 5 metres from any <b>network waterway</b> identified on the planning maps and in <b>Appendix 6.11.5.4</b>;</p> <p>Advice Note:</p> <ol style="list-style-type: none"> <li>1. The Canterbury Regional Council manages <b>earthworks</b> within 10 metres of other rivers and lakes and 20 metres of the coast and land use consent may be required from that Council.</li> </ol> <p>c. All <b>filling</b>, <b>excavation</b> or <b>disturbance of soil</b>:</p> <ol style="list-style-type: none"> <li>i. is not within the <b>dripline-tree protection zone radius</b> of a significant tree listed in <b>Appendix 9.4.7.1</b>; or</li> <li>ii. is not within any Site of Ecological Significance listed in Schedule A of <b>Appendix 9.1.6.1</b>; or</li> <li>iii. is not at or within 5 metres of: <ol style="list-style-type: none"> <li>A. any <b>heritage item</b> listed in <b>Appendix 9.3.7.2</b>, where the <b>heritage item</b> is on the same <b>site</b>, or</li> <li>B. a <b>site of Ngāi Tahu Cultural Significance</b> identified in <b>Schedule 9.5.6</b>.</li> </ol> </li> </ol> <p>d. Erosion and sediment control measures are implemented and maintained in accordance with Canterbury Regional Council’s Erosion and Sediment Control Guidelines for Small Sites to minimise erosion and the discharge of sediment laden water to surface water.</p> <p>e. All <b>filling</b>, <b>excavation</b> or <b>disturbance of soil</b> greater than 0.3m in depth shall be in accordance with New Zealand Standard <b>NZS 4431:1989</b> Code of Practice for Earth Fill for Residential Development. Certification is not required except as specified at activity specific standards k. and l. in <b>Table 5.4.4.1a</b>.</p> <p>f. All land repair works are to be managed in accordance with New Zealand Standard <b>NZS 6803:1999</b> Acoustics – Construction Noise and DIN 4150 1999-02 Structural Vibration.</p>

Activity	Activity specific standards
	<p>g. Land repair works involving mixing or insertion of <b>grout</b> shall not involve:</p> <ul style="list-style-type: none"> <li>i. mixtures with a flow time greater than 30 seconds when tested in accordance with the <b>grout</b> flow test at <b>NZS 3112: Part 1:1986</b> (Test 3) or a flowable concrete/ <b>grout</b> including cement and inert additives which exceed a diameter of 300mm when tested in accordance with the inverted cone test at <b>NZS 3112: Part 1:1986</b> (Test 11) except for <b>in-situ mixing</b>; or</li> <li>ii. injection of <b>grout</b> into the ground at a pressure of no more than 40 bar when measured at the pump.</li> </ul> <p>h. Where <b>grout</b> is deposited into land:</p> <ul style="list-style-type: none"> <li>i. using <b>in-situ mixing</b>, the <b>grout</b> shall be mixed evenly through the augured soil column and the percentage of <b>grout</b> within the augured soil column shall not exceed 20%; or</li> <li>ii. where <b>grout</b> is deposited into land using methods other than <b>in situ mixing</b>, the percentage of cement in the dry <b>grout</b> mixture shall not exceed 30%.</li> </ul> <p>i. Land repair materials shall consist only of:</p> <ul style="list-style-type: none"> <li>i. soil, gravel, rocks, concrete, sand, silt (such as exists on site already), or clean, inert material; or</li> <li>ii. cement and/or bentonite <b>grout</b> including inert additives; or</li> <li>iii. timber foundation piles; and shall not</li> <li>iv. include or disturb putrescible, pollutant, inflammable or hazardous components; and/or</li> <li>v. include <b>filling</b> which comprises more than 5% vegetation of any load by volume.</li> </ul> <p>j. Land repair works, other than dust and sediment control measures, shall not be undertaken outside of the hours of 7.30 to 18:00 Monday to Friday and 8.00 to 17:00 on Saturday. No works shall occur on public holidays.</p> <p>k. Where the land repair and <b>earthworks</b> are designed, supervised or certified by a Chartered Professional</p>

Activity	Activity specific standards
	<p>Engineer with experience in geotechnical engineering, or Professional Engineering Geologist (IPENZ Registered), at least 3 working days prior to commencing any work on the site, including stockpiling and preparatory works:</p> <ul style="list-style-type: none"> <li>i. written notice shall be provided to the Council informing it of the location of the land repair and the name and contact details of the supervising engineer; and</li> <li>ii. written notice shall be provided to any occupier of a residential unit adjoining the land repair site to inform them that the works will be taking place, the expected duration of the works and provide contact details of the site supervisor; and</li> <li>iii. a sign shall be erected at the front of the property including the name and contact details of the site supervisor.</li> </ul> <p>I. Where the land repair and earthworks are designed, supervised or certified by a Chartered Professional Engineer with experience in geotechnical engineering, or Professional Engineering Geologist (IPENZ Registered), a statement of professional opinion completed by a Chartered Professional Engineer with experience in geotechnical engineering must be provided to the Council within 3 months of the land repair being completed to the effect that the works will meet all applicable standards and requirements and be suitable for its intended purpose. This shall include as-built plans of the works.</p>

Standards where the land repair and earthworks are not designed, supervised or certified by a Chartered Professional Engineer with experience in geotechnical engineering. All activity specific standards in Rule 5.4.4.1 must also be met:

**Table 5.4.4.1b**

	Column A Max. Volume (Cumulative)	Column B Max. depth (m)	Column C Max. depth of filling (m) [below ground level]	Column D Filling (m) [above ground level]	Column E Setback from boundary

P1	50m <sup>3</sup> /site	0.6	0.6	0.3 max. depth; and 10 m <sup>3</sup> /site max. volume	Setback from boundary must be equivalent to or greater than the depth of filling or excavation.
P2	Not more than 10m <sup>3</sup> of grout/site	1.0	1.0	0.3m max. depth	

Standards where the land repair and earthworks are designed, supervised or certified by a Chartered Professional Engineer with experience in geotechnical engineering. All activity specific standards at Rule 5.4.4.1 must also be met:

**Table 5.4.4.1c**

	Column A Max. Volume (Cumulative)	Column B Max. depth (m)	Column C Max. depth of filling (m) [below ground level]	Column D Filling (m) [above ground level]	Column E Setback from boundary
P1	Nil	Nil	Nil	0.3 max. depth and 10m <sup>3</sup> /site max. volume	Nil
P2	Not more than 80m <sup>3</sup> of grout/site	Nil	Nil	Nil	1m

#### 5.4.4.2 Restricted discretionary activities

- a. The activities listed below are restricted discretionary activities in areas shown on the planning maps as a Flood Management Area (including the Te Waihora/Lake Ellesmere and Wairewa/Lake Forsyth Flood Management Areas).
- b. Exemptions from the restricted discretionary activities are listed in Rule 5.4.4.3.
- c. Discretion to grant or decline consent and impose conditions is restricted to the matters of discretion set out in the following table.

**Table 5.4.4.2a**

Activity		The Council's discretion shall be limited to the following matters:
RD1	a. Any filling or excavation undertaken to repair land used for residential purposes damaged by earthquakes that does not meet one or more of the	a. The Council's discretion shall be limited to the following matters:

	<p>activity specific standards for P1 or P2 set out in <a href="#">Rule 5.4.4.1</a>.</p> <p>b. Any application arising from this rule shall not be limited or publicly notified.</p>	<p>i. The matters for discretion reserved for RD2 set out in <a href="#">Rule 5.4.1.5</a>.</p> <p>b. These restricted discretionary activities will be assessed against the following criteria:</p> <p>i. The assessment criteria set out for RD2 in <a href="#">Rule 5.4.1.5</a></p>
--	--	---

### 5.4.4.3 Exemptions to Rules 5.4.4.1 and 5.4.4.2

- a. Works involving the establishment, repair or replacement of any permitted **utilities** or the maintenance of existing drains or ponds by a **utility** operator.
- b. Works permitted by or exempted from a building consent (including work forming part of foundations for a **building**) do not require resource consent under [Rules 5.4.4.1](#) or [5.4.4.2](#) where:
  - i. they meet the standards in column D of [Tables 5.4.4.1b](#) and [5.4.4.1c](#) in [Rule 5.4.4.1](#) controlling **filling** above **ground level** in a **Flood Management Area**; or
  - ii. they are designed, supervised and certified by a Chartered Professional Engineer with experience in geotechnical engineering, including where they exceed the criteria at columns A, B, C or E of [Tables 5.4.4.1b](#) and [5.4.4.1c](#) in [Rule 5.4.4.1](#); or
  - iii. they meet activity specific standards b. and c. of P1 and P2 in [Rule 5.4.4.1](#).
- c. Testing or investigation preceding land repairs or remediation as a result of land damaged by earthquakes is permitted provided it meets the activity specific standards for P1 and P2 in [Rule 5.4.4.1](#).
- d. **Filling** or **excavation** associated with the maintenance of flood protection works.
- e. Post holes for the erection of fences or for permitted or approved **buildings** and **signs**.
- f. Planting holes for trees and plants.

#### Clarification of rule

- a. For the purposes of this rule, the building consent platform extends to a maximum of 2.5m from the exterior wall of an enclosed structure or support structures of open structures.
- b. Measurement of volume shall include only areas which have been disturbed, including by **filling**, **excavation**, **soil mixing** or injection of materials. Soil above or between these areas which remains undisturbed does not form part of the allowable volume, including where those undisturbed soils are compacted or otherwise altered by the works.
- c. For the purposes of this rule, when land repairs are being undertaken over a number of properties at the same time and by the same contractor, the **site boundary** for the purpose of the setback is the outer perimeter of the properties which are subject to the land repair works.

#### Advice notes:

1. For the avoidance of doubt, where the **earthworks** are associated with the repair of land damaged by earthquakes and used for residential purposes in the zones listed in [Rule 5.4.4.1](#), [Rule 5.4.4](#) substitutes for all other **earthworks** rules in this [District Plan](#).
2. For the purposes of this rule, “repair of land used for residential purposes damaged by earthquakes” does not include repair of land on the Port Hills or [Banks Peninsula](#).
3. Those intending to do land repair **earthworks** are responsible for complying with the National Environmental Standard (NES) for Assessing and Managing Contaminants in Soil to Protect Human Health (2011). Such persons should contact the [Council](#) or Canterbury Regional Council to find out whether their land has been used for hazardous activities which might trigger the need for compliance with the NES.
4. Any vegetation removed during land repairs should not be replaced with pest species as listed in Appendix 1 to the [Infrastructure Design Standard \(Part 10\)](#). The [Council](#) prefers that replanting occurs in accordance with its Streamside Planting Guideline to ensure bank stability is not compromised.
5. Information regarding the disposal of excavated material and the Standards and Guidelines referenced in the rule is available from the [Council](#).
6. [Archaeological sites](#) are subject to a separate consent process under the [Heritage New Zealand Pouhere Taonga Act 2014](#). [The Heritage New Zealand Pouhere Taonga 2014](#) makes it unlawful for any person to destroy, damage or modify the whole or any part of an [archaeological site](#) without the prior authority of the Heritage New Zealand. This is the case regardless of whether the land on which site is located is designated, or the activity is permitted under the [District Plan](#) or Regional Plan or a resource or building consent has been granted. [The Heritage New Zealand Pouhere Taonga Act 2014](#) also provides for penalties for unauthorised destruction, damage or modification.

## 5.4.5 Activities and earthworks in the Flood Ponding Management Area

### 5.4.5.1 Permitted activities

- a. The activities listed below are permitted activities where the activity is located in the area shown on the planning maps as Flood Ponding Management Area, if they meet the activity standards set out in this table.
- b. Activities may also be restricted discretionary or non-complying as specified in [Rules 5.4.5.2](#) and [5.4.5.3](#).

Advice Note:

1. Consent may be required from Canterbury Regional Council for **earthworks** in a Flood Ponding Management Area.

Activity		Activity specific standards
<b>P1</b>	Filling or excavation associated with the maintenance of flood protection and bank erosion protection works; and the	Nil

Activity		Activity specific standards
	maintenance of existing drains or ponds.	
P2	Filling or excavation associated with utilities, or the replacement, repair or maintenance of existing utilities.	
P3	Filling or excavation for post holes for fences, planting holes, and excavation for approved wells.	
P4	Filling or excavation for the maintenance of existing farm tracks and farm yards, or the establishment of new farm tracks and farm yards.	a. Finished ground level shall be maintained to within 200mm of the natural ground level.
P5	Application of fertiliser, lime or other plant growth enhancers such as top soil, bark and trace elements. Advice Note: 1. Consent may be required from Canterbury Regional Council, pursuant to section 15 of the Act for the discharge of plant growth enhancers, including fertiliser, into or onto land.	a. Finished ground level shall be maintained to within 200mm of the natural ground level; and b. Filling is limited to a total volume of not more than 100m <sup>3</sup> per ha.; and c. For top soil, the maximum volume of filling shall be 100m <sup>3</sup> per site within any continuous period of 10 years.
P6	Filling or excavation for the purposes of establishing and maintaining access ways to a residential unit.	a. Finished ground level shall be maintained to within 200mm of the natural ground level, and b. Access ways shall be constructed so as not to impede the flow of surface water.
P7	Filling or excavation for the purposes of landscaping around a residential unit in association with domestic gardening.	a. The maximum volume of filling shall be 20m <sup>3</sup> per site per year and a maximum volume of filling of 100m <sup>3</sup> per site within any continuous period of 10 years.
P8	Filling and excavation for the maintenance or upgrade of existing roads on legal road.	a. The works shall not impede the flow of surface water.
P9	Filling that is not provided for under Rule 5.4.5.1 P 1-8 or P12.	a. Either the maximum depth of filling shall be 200mm, and b. The maximum volume of filling shall be 100m <sup>3</sup> per site within any continuous period of 10 years, and c. Finished ground level shall not exceed the surrounding land; or

Activity		Activity specific standards
		d. The <b>filling</b> has consent approval.
<b>P10</b>	<b>Excavation</b> for farm purposes that is not provided for under <b>Rule 5.4.5.1</b> P1-P4, P6-P8 or P12.	a. The excavated area is subsequently filled within the following year so that there is no net effect on flood storage.
<b>P11</b>	<b>Utilities</b>	a. The <b>ground floor area</b> of the <b>utility</b> does not exceed 10m <sup>2</sup> (except where the <b>utility</b> is a lattice tower for <b>electricity transmission</b> or <b>electricity distribution</b> purposes).
<b>P12</b>	<b>Excavation</b> and <b>filling</b> within the area identified in <b>Appendix 8.10.76d</b> – Cashmere/Worsleys Development Plan.	<p>a. The <b>excavation</b> and <b>filling</b> will not result in the reduction in the existing potential storage volume of water that is able to be retained within the development plan area, prior to any residential zone development, in a 0.2% <b>AEP</b> (1 in 500 year) event up to the existing Worsleys Road minimum centreline level of 18.89m (<b>Christchurch City Council Datum</b>). The design shall also accommodate additional storage for any additional stormwater that could be discharged from the development of the residential zones and <b>roads</b> in such a 0.2% <b>AEP</b> event.</p> <p>b. All <b>roads</b> are filled so that the crown of the <b>road</b> is no lower than <b>RL 18.7m</b> (<b>Christchurch City Council Datum</b>), except for the realigned Worsleys Road required in the Development Plan. The crown of Worsleys Road shall be no lower than <b>RL 18.89m</b> (<b>Christchurch City Council Datum</b>).</p> <p>c. The side slopes of all areas filled or excavated in accordance with a. and b. above shall not exceed an angle of 1 in 5.</p>
<b>P13</b>	The replacement or repair of <b>buildings</b> .	<p>a. The <b>ground floor area</b> of the replaced or repaired <b>building</b> is not greater than the <b>ground floor area</b> of the existing <b>building</b>.</p> <p>b. The replaced or repaired <b>building</b> is located in a position on the <b>site</b> that is no lower than the existing <b>building</b>.</p>
<b>P14</b>	<b>Residential unit</b> .	<p>a. The <b>residential unit</b> is either:</p> <ol style="list-style-type: none"> <li>i. on piles; or</li> <li>ii. has a maximum of 200m<sup>2</sup> <b>ground floor</b></li> </ol>

Activity		Activity specific standards
		<p>area.</p> <p>b. There is a maximum of one residential unit per site.</p>
P15	Farm buildings without floors.	Nil
P16	Accessory buildings without floors.	
P17	Farm buildings, or accessory buildings, with floors.	<p>a. The building:</p> <p>i. is on piles; or</p> <p>ii. has a maximum ground floor area of 200m<sup>2</sup>.</p> <p>b. There is a maximum of one accessory building or farm building per site up to 20 hectares and a maximum of one accessory building or farm building per additional 20 hectares of site.</p>
P18	Below-ground swimming pools.	Nil
P19	Above-ground swimming pools.	<p>a. The swimming pool is not larger than 200m<sup>2</sup>.</p> <p>b. There is no more than one swimming pool per 20 hectares of site.</p>

#### 5.4.5.2 Restricted discretionary activities

- a. The activities listed below are restricted discretionary activities where the activity is located in the area shown on the planning maps as Flood Ponding Management Area.
- b. Discretion to grant or decline consent and impose conditions is restricted to the matters of discretion as set out in the following table.

Activity		The Council's discretion shall be limited to the following matters:
RD1	<p>Filling and excavation within Henderson Basin for the creation and enhancement of:</p> <p>a. Water bodies, wetlands or public access ways associated with the recreation values of the water bodies or wetlands within the Basin; and</p> <p>b. stormwater treatment systems including water quality treatment,</p>	<p>a. The likely effects of proposed filling, or excavation or subdivision on the functioning of the ponding area or floodplain during flood periods including any compensatory storage proposed.</p> <p>b. Any potential impacts of excavation or filling or subdivision on the rate, level or volume of flood discharges to the Avon, Heathcote and Styx Rivers and their tributary streams and margins.</p>

	attenuation and compensatory storage.	<p>c. Any adverse effects on the natural qualities, <b>amenity values</b> or ecology of <b>water bodies</b> and <b>wetland</b> areas.</p> <p>d. In respect to the Lower Styx Ponding Area, any adverse effects likely on land as a result of tidal influences during flood periods including the potential for exacerbation of those effects with potential sea level rise.</p> <p>e. Any adverse effects on access for maintenance or flood protection works.</p>
<b>RD2</b>	<b>Utilities</b> that do not meet the activity specific standard in P11 of <b>Rule 5.4.5.1</b> .	f. The effectiveness and environmental impact of any measures that may be proposed to mitigate the effects of <b>filling</b> or <b>excavation</b> .
<b>RD3</b>	<b>Subdivision</b> within the area shown at <b>Appendix 8.10.7d</b> – Cashmere/Worsleys Development Plan Area for the following purposes: <ul style="list-style-type: none"> <li>a. <b>Roads</b>;</li> <li>b. ‘Land to Vest’ areas as shown on <b>Appendix 8.10.7d</b> This <b>allotment</b> will be transferred to the <b>Council</b>.</li> </ul>	g. Any beneficial effects, including the provision of public access, or the enhancement of the natural qualities, <b>amenity values</b> or ecology of <b>water bodies</b> and <b>wetland</b> areas.

### 5.4.5.3 Non-complying activities

- a. The activities listed below are non-complying activities where the activity is located in the area shown on the planning maps as Flood Ponding Management Area.

Activity	
<b>NC1</b>	Any <b>filling</b> or <b>excavation</b> activity listed in <b>Rule 5.4.5.1</b> that does not meet one or more of the activity specific standards, or any <b>filling</b> or <b>excavation</b> activity not listed in <b>Rules 5.4.5.1</b> or <b>5.4.5.2</b> .
<b>NC2</b>	Any <b>subdivision</b> which creates an additional vacant <b>allotment</b> or <b>allotments</b> from a <b>site</b> within a Flood Ponding Management Area shown on the planning maps except where: <ul style="list-style-type: none"> <li>a. the additional <b>allotment</b> or <b>allotments</b> is entirely outside the Flood Ponding Management Area; or</li> <li>b. if the additional <b>allotment</b> or <b>allotments</b> is partially within the Flood Ponding Management Area, the additional <b>allotment</b> or <b>allotments</b> contains a <b>net site area</b> capable of containing a complying <b>residential unit</b> entirely outside of the Flood Ponding Management Area.</li> </ul>
<b>NC3</b>	New <b>buildings</b> within a Flood Ponding Management Area shown on the planning maps, unless specified in P11, P13-17 and P19 in <b>Rule 5.4.5.1</b> or RD2 in <b>Rule 5.4.5.2</b> .
<b>NC4</b>	The replacement or repair of <b>buildings</b> that do not meet one or more of the activity specific standards in <b>Rule 5.4.5.1</b> .

## 5.4.6 Activities in the High Flood Hazard Management Area

### 5.4.6.1 Permitted activities

- a. The activities listed below are permitted activities where the activity is located in the area shown on the planning maps as [High Flood Hazard Management Area](#), if they meet the activity specific standards set out in this table.
- b. Activities may also be restricted discretionary or non-complying as specified in [Rules 5.4.6.2](#) and [5.4.6.3](#).

Activity		Activity specific standards
P1	The replacement or repair of <b>buildings</b> .	<p>a. The <b>ground floor area</b> of the replaced or repaired <b>building</b> is not greater than the <b>ground floor area</b> of the existing <b>building</b>.</p> <p>b. The replaced or repaired <b>building</b> is located in a position on the <b>site</b> that is no lower than the existing <b>building</b>.</p>
P2	The replacement and repair of residential units existing as at 4 September 2010 on sites in the Residential Unit Overlay identified in <a href="#">Appendix 5.8.2</a> .	<p>a. The ground floor area of the replaced or repaired residential unit is not greater than the ground floor area of the residential unit that existed as at 4 September 2010.</p> <p>b. The replaced or repaired residential unit is located in the same or similar position on the site as the residential unit that existed as at 4 September 2010.</p>
P3	<b>Utilities</b> .	<p>a. The <b>ground floor area</b> of the <b>utility</b> does not exceed 10m<sup>2</sup> (except where the <b>utility</b> is a lattice tower for <b>electricity transmission</b> or <b>electricity distribution</b> purposes).</p>
P4	Repair, rebuild and maintenance of <b>critical infrastructure</b> and associated <b>ancillary</b> structures.	Nil
P5	<b>Farm buildings</b> without floors in rural zones.	
P6	<b>Accessory buildings</b> without floors in rural zones.	
P7	<b>Farm buildings</b> , or <b>accessory buildings</b> , with floors in rural zones.	<p>a. The <b>building</b> is:</p> <ol style="list-style-type: none"> <li>i. on piles; or</li> <li>ii. has a maximum <b>ground floor area</b> of 200m<sup>2</sup>.</li> </ol>

Activity		Activity specific standards
		b. There is a maximum of one <b>accessory building</b> or <b>farm building</b> per <b>site</b> up to 20 hectares and a maximum of one <b>accessory building</b> or <b>farm building</b> per additional 20 hectares of <b>site</b> .
<b>P8</b>	Below-ground swimming pools in rural zones.	Nil.
<b>P9</b>	Above-ground swimming pools in rural zones.	a. The swimming pool is not larger than 200m <sup>2</sup> . b. There is no more than one swimming pool per 20 hectares of <b>site</b> .
<b>P10</b>	<b>Public amenities</b> within the Specific Purpose (Ōtākaro Avon River Corridor) Zone, excluding visitor information centres, public toilets and changing rooms.	Nil.

#### 5.4.6.2 Restricted discretionary activities

- a. The activities listed below are restricted discretionary activities where the activity is located in the area shown on the planning maps as **High Flood Hazard Management Area**.
- b. Discretion to grant or decline consent and impose conditions is restricted to the matters of discretion as set out in the following table.

Activity		The <b>Council's</b> discretion shall be limited to the following matters:
<b>RD1</b>	<b>Subdivision</b> within the area shown at <a href="#">Appendix 8.10.76d</a> – Cashmere/Worsleys Development Plan Area for the following purposes: <ol style="list-style-type: none"> <li>a. <b>Roads</b>;</li> <li>b. ‘Land to Vest’ areas as shown on <a href="#">Appendix 8.10.76d</a>. This <b>allotment</b> will be transferred to the <b>Council</b>.</li> </ol>	<ol style="list-style-type: none"> <li>a. The likely effects of the proposed <b>subdivision</b> on the <b>High Flood Hazard Management Area</b>.</li> <li>b. Any potential impacts of the <b>subdivision</b> on the rate, level or volume of flood within the <b>High Flood Hazard Management Area</b>.</li> <li>c. Whether the <b>subdivision</b> will increase the potential risk to people's safety, well-being and property.</li> </ol>
<b>RD2</b>	<b>Residential units</b> within the Residential Unit Overlay identified in <a href="#">Appendix 5.8.2</a> , including: <ol style="list-style-type: none"> <li>a. any new <b>residential unit</b>; or</li> <li>b. any replacement <b>residential unit</b>; or</li> <li>c. any addition to an existing <b>residential unit</b>.</li> </ol>	<ol style="list-style-type: none"> <li>a. The <b>Council's</b> discretion is limited to the following matters: <ol style="list-style-type: none"> <li>i. Setting of minimum floor levels.</li> <li>ii. Design of <b>buildings</b>.</li> <li>iii. Mitigation of the effects of flooding.</li> <li>iv. Level of intensification.</li> </ol> </li> </ol>

Activity		The Council's discretion shall be limited to the following matters:
	<p>other than as provided for by Rule 5.4.6.1 P1 or P2.</p> <p>Any application arising from this rule shall not be limited or publicly notified.</p>	<ul style="list-style-type: none"> <li>v. Safe ingress and egress.</li> <li>vi. Reducing the risk to people's safety, wellbeing and property resulting from the development.</li> </ul> <p>b. These restricted discretionary activities will be assessed against the following criteria:</p> <ul style="list-style-type: none"> <li>i. The type of foundation and structure proposed for the residential unit and the likely impact of the building with regard to flood storage and flow of water.</li> <li>ii. The frequency at which any proposed building or addition is predicted to be flooded, the extent of damage likely to occur in such an event and the potential for injury or risk to people's safety, well-being and property from such an event.</li> <li>iii. The ability to maintain safe access to and from the residential unit from the transport network with respect to design of the access and engineering solutions.</li> </ul>
<p><b>RD3</b></p>	<p>Any new building within the Specific Purpose (Ōtākaro Avon River Corridor) Zone, other than as provided for in Rule 5.4.6.1 P1, P3, P4 and P</p>	<ul style="list-style-type: none"> <li>a. Whether, based on an evaluation prepared by suitably qualified and experienced professionals: <ul style="list-style-type: none"> <li>i. The filling undertaken is adequate such that the building site no longer falls within the criteria contained in the definition of High Flood Hazard Management Area;</li> <li>ii. The proposal will avoid contributing to potential cumulative transfer of natural hazard risk to other people and property; and</li> <li>iii. functional access and egress will be maintained within and beyond the site during a hazard event; or</li> </ul> </li> <li>b. Whether, based on an evaluation prepared by suitably qualified and experienced professionals: <ul style="list-style-type: none"> <li>i. the structure proposed will maintain its sanitation, safety and functionality during an inundation hazard event or when there is a temporary loss of functionality it can be reinstated within a time appropriate to its use;</li> <li>ii. the proposal will avoid contributing to</li> </ul> </li> </ul>

Activity	The Council's discretion shall be limited to the following matters:
	<p data-bbox="927 293 1493 365">potential cumulative transfer of natural hazard risk to other people and property;</p> <ul style="list-style-type: none"> <li data-bbox="874 389 1501 499">iii. functional access and egress will be maintained within and beyond the site during a hazard event;</li> <li data-bbox="874 524 1493 674">iv. back-up servicing that does not rely on the Council's reticulated network is provided and is able to be used in the event the primary servicing fails;</li> <li data-bbox="874 698 1493 965">v. the proposal will not result in an unacceptable risk to life or property, recognising that, over time, predictions around sea level rise will result in changes to risk and considering the ability for the relocation or removal of structures and any consent monitoring proposed;</li> <li data-bbox="874 990 1493 1140">vi. the proposal will not exacerbate the effects of the natural hazard or generate the need for new mitigation works to protect the proposed structures; and</li> <li data-bbox="874 1164 1501 1520">vii. an adequate management plan is provided that includes where appropriate: <ul style="list-style-type: none"> <li data-bbox="935 1256 1501 1328">A. information on the hazards advice system being used to monitor anticipated hazards;</li> <li data-bbox="935 1352 1461 1424">B. evidence of alternative accommodation options available; and</li> <li data-bbox="935 1449 1469 1520">C. instructions on using the proposed back-up servicing.</li> </ul> </li> </ul>

### 5.4.6.3 Non-complying activities

- a. The activities listed below are non-complying activities where the activity is located within the area shown on the planning maps as High Flood Hazard Management Area.

Activity	
NC1	Any subdivision which creates an additional vacant allotment or allotments from a site within a High Flood Hazard Management Area shown on the planning maps except where:

	<p>a. the additional allotment or allotments is entirely within the Specific Purpose (Ōtākaro Avon River Corridor) Zone and is not intended for a habitable building or is intended for a building that has a resource consent under Rule 5.4.6.2 RD3; or</p> <p>b. the additional allotment or allotments is entirely outside the High Flood Hazard Management Area; or</p> <p>c. if the additional allotment or allotments is partially within the High Flood Hazard Management Area, the additional allotment or allotments contains a net site area capable of containing a complying residential unit entirely outside of the High Flood Hazard Management Area.</p>
<b>NC2</b>	New buildings within a High Flood Hazard Management Area shown on the planning maps, unless specified in P1 – P7 or P9, or P10 in Rule 5.4.6.1, or RD2 – RD3 in Rule 5.4.6.2.
<b>NC3</b>	The replacement or repair of buildings that do not meet one or more of the activity specific standards in Rule 5.4.6.1, unless specified in RD2 in Rule 5.4.6.2.
<b>NC4</b>	Change in use of a site that increases the occupancy of the site, unless specified in P1 or P2 in Rule 5.4.6.1, or RD2, or RD3 in Rule 5.4.6.2.

## 5.4A Rules – Qualifying Matter Coastal Hazard Management Areas and Qualifying Matter Tsunami Management Area

### 5.4A.1 Permitted activities

- a. There are no permitted activities.

### 5.4A.2 Controlled activities

- a. The activities listed below are controlled activities.

	<u>Activity</u>	<u>The matters over which Council reserves its control</u>
<u>C1</u>	a. <u>The construction of replacement buildings located in the area shown on the planning maps as Qualifying Matter Coastal Hazard Medium Risk Management Area.</u>	<p>a. <u>The number and size of buildings and structures, siting of buildings and structures, design, and building materials with regard to the level of mitigation of the potential adverse effects from coastal hazards.</u></p> <p>b. <u>Setting of minimum floor levels to mitigate the effects of inundation.</u></p> <p>c. <u>There is adequate provision for the timely relocation or removal of buildings and structures, or cessation of activity, and remediation of the site, and mechanisms to ensure this occurs, if considered necessary due to the level of risk.</u></p>
<u>C2</u>	a. <u>Earthworks associated with Rule 5.4A.2 C1.</u>	a. <u>The timing, scale, duration, and location of earthworks, and method of earthworks to mitigate the effects of coastal hazards and avoid the transfer of risk to another site.</u>
<u>C3</u>	a. <u>Stormwater management area associated with Rule 5.4A.2 C1.</u>	<p>a. <u>The proposed stormwater management for the site:</u></p> <p>i. <u>takes into account the effects of sea level rise;</u></p> <p>ii. <u>mitigates the effects on water quality;</u></p> <p>iii. <u>mitigates the effects of erosion;</u></p> <p>iv. <u>mitigates increased run off to areas outside the site boundary to the greatest extent reasonable;</u></p> <p>and</p> <p>v. <u>avoids the transfer of risk to another site.</u></p>

### 5.4A.3 Restricted discretionary activities

- a. The activities listed below are restricted discretionary activities.

	<u>Activity</u>	<u>The Council's discretion shall be restricted to the following matters:</u>
<u>RD1</u>	a. <u>The construction of replacement buildings,</u>	a. <u>Whether the development or use of the site can adequately mitigate the adverse effects of coastal</u>

	<p><u>accessory buildings, and extensions/additions to existing buildings located in the area shown on the planning maps as Qualifying Matter Coastal Hazard High Risk Management Area.</u></p> <p>b. <u>The construction of accessory buildings and extensions/additions to existing buildings located in the area shown on the planning maps as Qualifying Matter Coastal Hazard Medium Risk Management Area.</u></p>	<p>hazards on people, property, infrastructure and the environment.</p> <p>b. <u>Whether the number and size of buildings and structures, siting of buildings and structures, design, and building materials are appropriate for the site considering the risk of coastal hazards, and provide appropriate mitigation to the potential adverse effects from coastal hazards.</u></p> <p>c. <u>Whether the proposed floor levels will mitigate the effects of inundation including with sea level rise.</u></p> <p>d. <u>Whether there is adequate provision for the timely relocation or removal of buildings and structures, or cessation of activity, and remediation of the site, and mechanisms to ensure this occurs, if considered necessary due to the level of risk.</u></p>
RD2	a. <u>Earthworks associated with Rule 5.4A.3 RD1.</u>	a. <u>Whether the timing, duration, scale and location of earthworks, and method of earthworks are appropriate to mitigate the effects of coastal hazards, and avoids the transfer of risk to another site.</u>
RD3	a. <u>Stormwater management area associated with Rule 5.4A.3 RD1.</u>	<p>a. <u>Whether the proposed stormwater management for the site:</u></p> <p>i. <u>takes into account the effects of sea level rise;</u></p> <p>ii. <u>mitigates the effects on water quality; and</u></p> <p>iii. <u>mitigates the effects of erosion;</u></p> <p>iv. <u>mitigates increased run off to areas outside the site boundary to the greatest extent reasonable.</u></p>

#### 5.4A.4 Discretionary activities

- a. The activities listed below are discretionary activities.

	<u>Activity</u>
D1	a. <u>The addition of a new building, other than the construction of accessory buildings, extensions/additions to existing buildings, and the replacement of an existing building, located in the area shown on the planning maps as Qualifying Matter Coastal Hazard Medium Risk Management Area.</u>

#### 5.4A.5 Non-complying activities

- a. The activities listed below are non-complying activities.

	<u>Activity</u>
NC1	a. <u>The addition of a building, other than the construction of accessory buildings, extensions/additions to existing buildings, and the replacement of an existing</u>

	<u>building</u> , located in the area shown on the planning maps as <u>Qualifying Matter Coastal Hazard High Risk Management Area</u> .
<b>NC2</b>	a. <u>Subdivision</u> located in the area shown on the planning maps as <u>Qualifying Matter Coastal Hazard Medium Risk Management Area and Qualifying Matter Coastal Hazard High Risk Management Area</u> .
<b>NC3</b>	a. <u>Development, subdivision</u> and land use that would provide for residential intensification of any <u>site</u> within the <u>Qualifying Matter Tsunami Management Area</u> except that permitted or controlled in <u>Rule 14.4.1</u> .

#### **5.4A.6 Prohibited activities**

- a. There are no prohibited activities.

## 5.5 Rules - Liquefaction hazard

- a. Liquefaction is a process that can occur during strong earthquake shaking which causes loss of stiffness and strength in generally loosely consolidated fine grained water saturated soils and can result in ground damage from lateral spreading, settlement, ground cracking, sand boils and deposition of sediment, as well as localised flooding.

### 5.5.1 Permitted activities

- a. All activities in the Liquefaction Management Area are a permitted activity unless specified in [Rules 5.5.2](#) or [5.5.3](#), or as otherwise specified elsewhere in the [District Plan](#).

### 5.5.2 Controlled activities

- a. The activities listed below are controlled activities within the area shown on the planning maps as the Liquefaction Management Area.
- b. Discretion to impose conditions is restricted to the matters over which control is reserved as set out in the following table.
- c. Where [subdivision](#) is specified, a subdivision consent is also required under [Chapter 8](#) Subdivision, Development and Earthworks.
- d. There may be other areas that are not identified at the district scale that are susceptible to liquefaction risk based on site specific characteristics – these may require specific geotechnical investigations as part of [subdivision](#) to satisfy the [Council](#) with respect to [Section 104](#) and [Section 106](#) of the [RMA](#).

Table 5.5.2a

Activity	The matters over which <a href="#">Council</a> reserves its control
<p><b>C1</b></p> <ul style="list-style-type: none"> <li>a. Any <a href="#">subdivision</a> which creates an additional vacant <a href="#">allotment</a> or <a href="#">allotments</a> in the Liquefaction Management Area.</li> <li>b. Any resource consent application arising from this rule shall not be limited or publicly notified.</li> </ul>	<ul style="list-style-type: none"> <li>a. The <a href="#">Council</a>'s control is limited to the following matters:               <ul style="list-style-type: none"> <li>i. location, size and design of <a href="#">allotments</a>, structures, <a href="#">roads</a>, <a href="#">access</a>, services or foundations as they relate to the liquefaction hazard;</li> <li>ii. timing, location, scale and nature of <a href="#">earthworks</a> as they relate to the liquefaction hazard; and</li> <li>iii. liquefaction hazard remediation methods.</li> </ul> </li> <li>b. These controlled activities will be assessed against the following criteria.               <ul style="list-style-type: none"> <li>i. Whether techniques proposed for remediation and/or mitigation of the effects of any liquefaction</li> </ul> </li> </ul>

Activity		The matters over which Council reserves its control
	<p>Advice Note:</p> <p>1. This rule does not apply to <b>boundary</b> adjustments, amalgamations, or the creation of unit titles.</p>	<p>hazard identified are appropriate, including but not limited to:</p> <p>A. provision for ground-strengthening, foundation design, provision of resilient services and the ability of these to be incorporated into the subdivision consent as conditions or consent notices; and</p> <p>B. setbacks in relation to any waterway or <b>water body</b>, or any sharp change in ground elevation, sloping ground or free face. Alternatively, whether ground-strengthening or other proposed engineering or geotechnical solutions are identified to address any identified potential for lateral spread.</p> <p>ii. The extent to which the layout of the <b>subdivision</b> in relation to the liquefaction hazard is appropriate, including the proposed location of <b>earthworks, roads, access</b>, servicing and <b>building</b> platforms in relation to the liquefaction hazards identified.</p> <p>iii. The effect of the remediation and/or mitigation on the reasonable use of the <b>site</b>.</p>

### 5.5.3 Restricted discretionary activities

- a. The activities listed below are restricted discretionary activities in any zone within the area shown on the planning maps as the Liquefaction Management Area.
- b. Discretion to grant or decline consent and impose conditions is restricted to the matters of discretion set out in the following table.

Table 5.5.3a

Activity		The Council's discretion shall be limited to the following matters:
<b>RD1</b>	<p>a. Any activity located on a <b>site</b> with an area of 1500m<sup>2</sup> or more, qualifying as a controlled or restricted discretionary activity under any of the</p>	<p>a. The Council's discretion is limited to the following matters:</p> <p>i. Location, siting and layout, design of <b>buildings, car-parking areas, access</b>, services or foundations as they relate to the liquefaction hazard</p> <p>ii. Timing, location, scale and nature of <b>earthworks</b> as they relate to the liquefaction hazard</p>

Activity		The Council's discretion shall be limited to the following matters:
	<p>following residential rules:</p> <p><del>i. Enhanced Development Mechanism – Rule 14.13.2.3 RD1, RD2;</del></p> <p><del>ii. Community Housing Redevelopment Mechanism – Rule 14.14.1.3 RD1, RD2;</del></p> <p><del>iii. i. Residential Suburban Zone and Residential Suburban Density Transition Zone - Rule 14.4.1.3 RD7, RD8, RD10;</del></p> <p><del>iv. ii. Residential Medium Density Residential Zone - Rule 14.5.1.3 RD2;</del></p> <p><del>v. iii. Residential Banks Peninsula Zone - Rule 14.8.1.3 RD14</del></p> <p><del>vi. iv. Residential Neighbourhood Zone – Future Urban Zone – Rule 14.12.1.2 C1 or Rule 14.12.1.3 RD3;</del></p> <p>b. Any application arising from this rule in respect to the Enhanced Development Mechanism or the Community Housing Redevelopment Mechanism shall not be limited or publicly notified.</p>	<p>iii. Liquefaction hazard remediation methods</p> <p>b. These restricted discretionary activities will be assessed against the following criteria:</p> <p>i. Whether techniques proposed for remediation and mitigation of the effects of any liquefaction hazard identified are appropriate, including but not limited to:</p> <p>A. Provision for ground-strengthening, foundation design, and provision of resilient services</p> <p>B. Setbacks in relation to any waterway or water body, or any sharp change in ground elevation, sloping ground or free face. Alternatively, whether ground-strengthening or other proposed engineering or geotechnical solutions are identified to address any identified potential for lateral spread.</p> <p>ii. The extent to which the siting and layout of the proposal is appropriate, including the proposed location of buildings, earthworks, car parking areas, servicing, access and building platforms in relation to the liquefaction hazards identified.</p>

## 5.6 Rules - Slope instability

### 5.6.1 Activity status for Slope Instability Management Areas

#### 5.6.1.1 Activity status for Slope Instability Management Areas excluding land within the Specific Purpose (Lyttelton Port) Zone

- The activities listed below have the activity status listed within each Slope Instability Management Area, and are subject to any activity status, rules and any standards specified elsewhere in the [District Plan](#) for that activity.
- In relation to controlled activities, discretion to impose conditions is restricted to the matters over which control is reserved as set out in [Rule 5.6.1.4](#) and [5.6.1.5](#) as applicable.
- In relation to restricted discretionary activities, discretion to grant or decline consent and impose conditions is restricted to the matters of discretion set out in [Rule 5.6.1.6](#).
- Where [subdivision](#) is specified, a subdivision consent is also required under the provisions of [Chapter 8](#).

Table 5.6.1.1a

Activity	Cliff Collapse Mgmt Area 1	Cliff Collapse Mgmt Area 2. For exceptions, refer to <a href="#">Rule 5.6.1.2</a>	Rockfall Mgmt Area 1. For exceptions, refer to <a href="#">Rule 5.6.1.2</a>	Rockfall Mgmt Area 2. For exceptions, refer to <a href="#">Rule 5.6.1.2</a>	Mass Mvmt Mgmt Area 1	Mass Mvmt Mgmt Areas 2 & 3	Remainder of Port Hills and Banks Peninsula Slope Instability Mgmt Area	
Key: P = Permitted; RD = Restricted Discretionary; D = Discretionary; NC = Non-complying; PR = Prohibited.								
a.	<a href="#">Subdivision</a>	PR1/NC1*	NC2	NC3	RD1	NC4	RD2	RD3
b.	<a href="#">Earthworks</a> except where specifically provided below in <a href="#">Rule 5.6.1.1</a>	PR2	NC5	NC6	RD4	NC7	RD5	Refer to relevant chapters within zone and/or district wide provisions applying to the <a href="#">sites</a> within this area
c.	<a href="#">Hazard mitigation works</a> or hazard removal works, including <a href="#">earthworks</a>	PR3	NC8	RD6	RD7	NC9	RD8	RD9

Activity	Cliff Collapse Mgmt Area 1	Cliff Collapse Mgmt Area 2. For exceptions, refer to Rule 5.6.1.2	Rockfall Mgmt Area 1. For exceptions, refer to Rule 5.6.1.2	Rockfall Mgmt Area 2. For exceptions, refer to Rule 5.6.1.2	Mass Mvmt Mgmt Area 1	Mass Mvmt Mgmt Areas 2 & 3	Remainder of Port Hills and Banks Peninsula Slope Instability Mgmt Area
associated with those works, unless provided for in d							
d. Hazard mitigation works to protect infrastructure, including earthworks associated with those works	RD10	RD11	RD12	RD13	RD14	RD15	RD16
e. Demolition of buildings	RD17	RD18	RD19	RD20	RD21	RD22	P1
f. Repair and maintenance of existing infrastructure, including minor upgrading of the existing electricity network	P2	P3	P4	P5	P6	P7	P8
g. Earthworks associated with activities listed in f. above	C1	C2	C3	C4	C5	C6	P9
h. Upgrading of existing infrastructure or development of new infrastructure (where there is a functional need to locate in the overlay), including earthworks	RD23	RD24	RD25	RD26	RD27	RD28	Refer to relevant chapters within zone and/or district wide provisions applying to the sites within this area

Activity	Cliff Collapse Mgmt Area 1	Cliff Collapse Mgmt Area 2. For exceptions, refer to Rule 5.6.1.2	Rockfall Mgmt Area 1. For exceptions, refer to Rule 5.6.1.2	Rockfall Mgmt Area 2. For exceptions, refer to Rule 5.6.1.2	Mass Mvmt Mgmt Area 1	Mass Mvmt Mgmt Areas 2 & 3	Remainder of Port Hills and Banks Peninsula Slope Instability Mgmt Area	
	associated with these works.							
i.	Retaining walls which are both less than 6 m <sup>2</sup> in area and less than 1.8 metres in height including earthworks associated with those works.	RD29	RD30	RD31	P10	RD32	P11	P12
j.	Signage and fencing for warning or excluding the public, including post holes associated with those works.	RD33	P13	P14	P15	P16	P17	Refer to relevant chapters within zone and/or district wide provisions applying to the sites within this area
k.	Hazard mitigation works and associated earthworks and planting in accordance with the Port Hills Parks and Tracks Reopening Process (dated 19 December 2012)	NC10	P18	P19	P20	NC11	P21	P22
l.	Recreation activities within parks and reserves and associated park management activities,	NC12	P23	P24	P25	NC13	P26	Refer to relevant chapters within zone and/or district wide provisions applying to the

Activity	Cliff Collapse Mgmt Area 1	Cliff Collapse Mgmt Area 2. For exceptions, refer to Rule 5.6.1.2	Rockfall Mgmt Area 1. For exceptions, refer to Rule 5.6.1.2	Rockfall Mgmt Area 2. For exceptions, refer to Rule 5.6.1.2	Mass Mvmt Mgmt Area 1	Mass Mvmt Mgmt Areas 2 & 3	Remainder of Port Hills and Banks Peninsula Slope Instability Mgmt Area	
	including grazing and track repair.						sites within this area	
m.	Farm buildings and farm tracks, including earthworks associated with these works.	NC14	NC15	RD34	RD35, except that farm tracks up to 2 metres wide shall be permitted.	NC16	RD36	Refer to relevant chapters within zone and/or district wide provisions applying to the sites within this area
n.	Any building or structure not listed in activities a. to m. of Rule 5.6.1.1	PR4	NC17	NC18	RD37	NC19	RD38	Refer to relevant chapters within zone and/or district wide provisions applying to the sites within this area
o.	Any other activity not otherwise listed in this table.	NC20	NC21	NC22	RD39	NC23	RD40	Refer to relevant chapters within zone and/or district wide provisions applying to the sites within this area

- e. Any resource consent application arising from C1-6, or RD1–RD40 set out in Rule 5.6.1.1 above shall not be limited or publicly notified.

\* Prohibited where site subject to proposed subdivision is solely located within Cliff Collapse Management Area 1; non-complying activity where it is proposed to subdivide off land within Cliff Collapse Management Area 1 from an area of land not within Cliff Collapse Management Area 1.

### 5.6.1.2 Exceptions to Rule 5.6.1.1 — AIFR Certificate

- a. The Council will issue an AIFR Certificate (which will be valid for 2 years from the date of issue) which specifies the calculated AIFR from i. and ii. below for an identified area of land in Rockfall

Management Area 1, Rockfall Management Area 2 and/or Cliff Collapse Management Area 2 only, when the following procedure is undertaken and the requirements of the procedure are satisfied:

- i. The Council has received a report, in respect of an identified area of land, prepared by a Chartered Professional Engineer with requisite experience in geotechnical engineering or a Professional Engineering Geologist (IPENZ registered), which calculates the AIFR from rockfall and/or cliff collapse for the identified land in the following manner:<sup>7</sup>
  - A. If the land is in Rockfall Management Area 1:
    - I. Apply the method for assessing the risk as set out in the *GNS Science Consultancy Report 2011/311 Port Hills Slope Stability: Pilot Study for assessing life-safety risk from rockfalls (boulder rolls)*, and any subsequent updates to this report by GNS Science, using the parameters listed in the Table in Policy 5.2.2.4.1.a for Rockfall Management Area 1 along with any relevant site-specific information, and other parameters in the GNS Science report (calculation 1(a)).
    - II. If the risk (AIFR) resulting from calculation 1(a) is less than that shown in the Table in Policy 5.2.2.4.1.a for Rockfall Management Area 1 ( $\geq 10^{-4}$ ), then using the same method set out in the *GNS Science Consultancy Report 2011/311 Port Hills Slope Stability: Pilot Study for assessing life-safety risk from rockfalls (boulder rolls)*, and any subsequent updates to this report by GNS Science, calculate the AIFR using the parameters listed in the Table in Policy 5.2.2.4.1.a for Rockfall Management Area 2 along with all relevant site-specific information, and other parameters listed in the GNS Science report (calculation 1(b)).
  - B. If the land is in Rockfall Management Area 2:
    - I. Apply the method for assessing the risk as set out in the *GNS Science Consultancy Report 2011/311 Port Hills Slope Stability: Pilot Study for assessing life-safety risk from rockfalls (boulder rolls)*, and any subsequent updates to this report by GNS Science, using the parameters listed in the Table in Policy 5.2.2.4.1.a for Rockfall Management Area 2 along with all relevant site-specific information, and other parameters in the GNS Science report (calculation 2(a)).
  - C. If the land is in Cliff Collapse Management Area 2:
    - I. Apply the method for assessing the risk as set out in the GNS Science Consultancy Reports *2012/57 Port Hills Slope Stability: Pilot Study for assessing life-safety risk from cliff collapse* and *2012/124 Port Hills Slope Stability: Life-safety risk from cliff collapse in the Port Hills*, and any subsequent updates to those reports by GNS Science, using the parameters listed in the Table in Policy 5.2.2.4.1.a for Cliff Collapse Management Area 2 along with all relevant site-specific information, and other parameters in the GNS Science Consultancy Reports (calculation 3(a)).

AND

- ii. The Council has commissioned and received a peer review report from a Chartered Professional Engineer with requisite experience in geotechnical engineering or a Professional

---

<sup>7</sup> The calculation shall not take account of hazard mitigation works.

Engineering Geologist (IPENZ registered)\*\*, which concurs with the application of the method required in i. above, and with the calculated AIFR(s) for the identified land.

\*\*The peer reviewer must not, at the time of undertaking the review, be employed by either:  
a) the same company as the company that authored the report received in i. above, or b) the Council.

- b. Where a valid AIFR Certificate has been issued by the Council for an identified area of land, in accordance with the procedure described in Rule 5.6.1.2a. above, the activity status (for activities listed in Table 5.6.1.1a) that applies to that land shall be that which applies to the Slope Instability Management Area specified in Table 5.6.1.2a. below. An AIFR Certificate is valid for 2 years from the date of issue. If the activity is commenced (in the case of a permitted activity) or a resource consent application is lodged within 2 years from the date of issue of the AIFR Certificate, no further Certificate is required after the 2 year term expires.

<sup>7</sup> The calculation shall not take account of hazard mitigation works.

**Table 5.6.1.2a**

Slope instability hazard management area applying to the land on the planning maps	AIFR as specified in the site-specific AIFR Certificate		Slope Instability Management Area for the purpose of determining activity status for activities on the land (Table 5.6.1.1a)
<b>Rockfall Management Area 1</b>	Result of calculation 1(a)	$\geq 10^{-4}$	Rockfall Management Area 1
	Result of calculation 1(b) where required	$\geq 10^{-4}$	Rockfall Management Area 2
		$< 10^{-4}$	Remainder of Port Hills and Banks Peninsula
<b>Rockfall Management Area 2</b>	Result of calculation 2(a)	$\geq 10^{-4}$	Rockfall Management Area 2
		$< 10^{-4}$	Remainder of Port Hills and Banks Peninsula
<b>Cliff Collapse Management Area 2</b>	Result of calculation 3(a)	$\geq 10^{-4}$	Cliff Collapse Management Area 2
		$< 10^{-4}$	Remainder of Port Hills and Banks Peninsula

Advice note:

1. Calculated AIFRs specified in issued, valid AIFR Certificates for identified areas of land, and valid certificates themselves, will be made freely available to the public, recorded in the Council's Geographical Information System and provided in Land Information Memoranda.
2. Changes to the District Plan will be regularly notified, as required, to change the planning maps, in order to reflect updated information regarding life-safety risk from rockfall and/or cliff collapse from issued AIFR Certificates.

### 5.6.1.3 Activity status for Slope Instability Management Areas within the Specific Purpose (Lyttelton Port) Zone

- a. The activities listed below have the activity status listed within each Slope Instability Management Area.
- b. In relation to controlled activities, discretion to impose conditions is restricted to the matters over which control is reserved as set out in [Rule 5.6.1.4](#) and [5.6.1.5](#) as applicable.
- c. In relation to restricted discretionary activities, discretion to grant or decline consent and impose conditions is restricted to the matters of discretion set out in [Rule 5.6.1.6](#).
- d. Where [subdivision](#) is specified, a subdivision consent is also required under the provisions of [Chapter 8](#).

**Table 5.6.1.3a**

	<b>Activity</b>	<b>Cliff Collapse Mgmt Area 1</b>	<b>Cliff Collapse Mgmt Area 2</b>	<b>Rockfall Mgmt Area 1</b>	<b>Rockfall Mgmt Area 2</b>	<b>Remainder of Port Hills and Banks Peninsula Slope Instability Mgmt Area</b>
a.	<a href="#">Subdivision</a>	C7	C8	C9	C10	Refer to relevant chapters within zone and/or district wide provisions applying to the <a href="#">sites</a> within this area
b.	<a href="#">Earthworks</a> except as provided for below	NC24	RD41	C11	C12	Refer to relevant chapters within zone and/or district wide provisions applying to the <a href="#">sites</a> within this area
c.	<a href="#">Hazard mitigation works</a> , including <a href="#">earthworks</a> associated with those works	C13	C14	C15	C16	Refer to relevant chapters within zone and/or district wide provisions applying to the <a href="#">sites</a> within this area
d.	Demolition of <a href="#">buildings</a>	C17	C18	C19	C20	Refer to relevant chapters within zone and/or district wide provisions applying to the <a href="#">sites</a> within this area

	Activity	Cliff Collapse Mgmt Area 1	Cliff Collapse Mgmt Area 2	Rockfall Mgmt Area 1	Rockfall Mgmt Area 2	Remainder of Port Hills and Banks Peninsula Slope Instability Mgmt Area
e.	Repair and maintenance of existing infrastructure, buildings, and access ways, including minor upgrading of the existing electricity network.	P1	P2	P3, includes earthworks associated with these works on flat land or where the earthworks are less than 10m <sup>3</sup> cut or fill on sloping land.	P4, includes earthworks associated with these works on flat land or where the earthworks are less than 10m <sup>3</sup> cut or fill on sloping land.	P
f.	Earthworks associated with the activities listed in e above unless identified as permitted.	C21	C22	C23	C24	P
g.	Upgrading of existing infrastructure, buildings, and access ways including associated earthworks, provided such upgrades are limited to an increase in capacity, efficiency or security of an existing structure or route	D1	RD42	RD43	RD44	Refer to relevant chapters within zone and/or district wide provisions applying to the sites within this area

	<b>Activity</b>	<b>Cliff Collapse Mgmt Area 1</b>	<b>Cliff Collapse Mgmt Area 2</b>	<b>Rockfall Mgmt Area 1</b>	<b>Rockfall Mgmt Area 2</b>	<b>Remainder of Port Hills and Banks Peninsula Slope Instability Mgmt Area</b>
h.	Construction of new non-habitable** buildings or structures used for storage or infrastructure	D2	RD45	RD46	RD47	Refer to relevant chapters within zone and/or district wide provisions applying to the sites within this area
i.	Construction of new retaining walls	RD48	C25	P5	P6	Refer to relevant chapters within zone and/or district wide provisions applying to the sites within this area
j.	Quarrying and associated haul road formation on land below Sumner Rd	Not applicable	Not applicable	C26	C27	Refer to relevant chapters within zone and/or district wide provisions applying to the sites within this area
k.	Bulk storage of cargo or construction material, outdoors on flat land	RD49	C28	P7	P8	Refer to relevant chapters within zone and/or district wide provisions applying to the sites within this area
l.	Signage and fencing for warning or excluding the public including postholes associated with those works	P9	P10	P11	P12	Refer to relevant chapters within zone and/or district wide provisions applying to the sites within this area

	Activity	Cliff Collapse Mgmt Area 1	Cliff Collapse Mgmt Area 2	Rockfall Mgmt Area 1	Rockfall Mgmt Area 2	Remainder of Port Hills and Banks Peninsula Slope Instability Mgmt Area
m.	Minor earthworks associated with tree planting, ecological restoration and the formation and maintenance of pedestrian walking and cycle tracks	D3	P13	P14	P15	Refer to relevant chapters within zone and/or district wide provisions applying to the sites within this area
n.	Any activities not otherwise listed above, including buildings not otherwise provided for under h	NC25	NC26	NC27	D4	Refer to relevant chapters within zone and/or district wide provisions applying to the sites within this area

e. Any resource consent application arising from any controlled or restricted discretionary activities set out in Rule 5.6.1.3 above shall not be limited or publicly notified.

**\*\*Note:** for the purpose of Rule 5.6.1.3h, ‘non-habitable’ buildings means those buildings or structures where the building is not designed for human occupation and will not be used for human occupancy. Examples of such buildings include bulk storage silos, tanks, plant rooms and electricity substations.

#### 5.6.1.4 Slope Instability Management Areas — C1 to C6 matters of control

a. The Council’s control is limited to the following matters:

- i. timing, location, scale and nature of earthworks;
- ii. earthworks method; and
- iii. mitigation of effects as they impact slope instability hazards.

b. Controlled activities C1 to C6 will be assessed against the following criteria:

- i. Whether proposed earthworks could trigger slope instability or exacerbate risk posed by natural hazard(s) to people or property, and any measures required to avoid or mitigate that risk.
- ii. Measures proposed to reinstate the excavated or filled area on completion of the earthworks to reduce the natural hazard risk(s) and ensure long-term land stability.

- iii. Whether the **earthworks** could have any adverse effects as a result of disturbance to drainage patterns and any measures required to avoid or mitigate such effects.

### 5.6.1.5 Slope Instability Management Areas — C7 to C28 matters of control

- a. The **Council's** control is limited to the following matters:
  - i. effects of natural hazards on people and property;
  - ii. location, size and design of **allotments**, structures, **roads**, **access**, services or foundations in relation to natural hazard risk;
  - iii. location, scale and design of **buildings** in relation to natural hazard risk;
  - iv. clearance or retention of vegetation or other natural features that mitigate natural hazard risk;
  - v. timing, location, scale and nature of **earthworks**;
  - vi. **earthworks** method;
  - vii. potential for the proposal to exacerbate natural hazard risk;
  - viii. benefits of infrastructure and performance of **critical infrastructure** following a natural hazard event; and
  - ix. mitigation of effects as they impact slope instability hazards.
- b. Controlled activities C7 to C28 will be assessed against the following criteria:
  - i. Whether the proposal and associated **hazard mitigation works**:
    - A. can be shown, based on evaluation by a Chartered Professional Engineer with experience in geotechnical engineering, using best practice methods, to increase the stability of land and/or protect structures and **buildings** and their occupants;
    - B. can be shown, based on evaluation by a Chartered Professional Engineer with experience in geotechnical engineering, using best practice methods, to achieve an acceptable risk to life or property, including the extent to which an **Annual Individual Fatality Risk** of  $10^{-4}$  (1 in 10,000) or better can be achieved; and
    - C. will have appropriate monitoring procedures applied, with inspections and maintenance undertaken and reported to the **Council**.
  - ii. Whether, due to the sensitive nature of the proposed activity (for example, childcare centre, playground, **hospital**), an **Annual Individual Fatality Risk** lower than  $10^{-4}$  is appropriate.
  - iii. Whether development of the **site** transfers risk to another **site**.
  - iv. Whether the location and design of proposed **building** platforms, **access**, **earthworks**, retaining walls and services to the **site** are the most appropriate considering the risk of natural hazards on the **site**.
  - v. Provision for ground-strengthening, foundation design, protection structures and the ability of these to be incorporated into the subdivision consent as conditions or consent notices.

- vi. The extent that surface or subsurface drainage patterns and stormwater management are impacted as a result of **hazard mitigation works**, and whether these have an effect on the **site** or surrounding **sites**.
- vii. Where **critical infrastructure** is involved, whether the infrastructure is designed in a way to continue to operate safely in the event of a significant natural hazard occurring, including containment of any **hazardous substances** associated with that infrastructure.
- viii. For infrastructure generally, the extent of benefits associated with that infrastructure, whether there is a functional or operational requirement for that location and whether there are any practical alternatives.
- ix. Whether or not the work would be carried out under the supervision of either a Chartered Professional Engineer with experience in geotechnical engineering or a Professional Engineering Geologist (IPENZ registered).

#### **5.6.1.6 Slope Instability Management Areas — RD1 to RD49 matters of discretion**

- a. The **Council's** discretion is limited to the following matters:
  - i. effects of natural hazards on people and property;
  - ii. location, size and design of **allotments**, structures, **roads**, **access**, services or foundations in relation to natural hazard risk;
  - iii. location, scale and design of **buildings** in relation to natural hazard risk;
  - iv. clearance or retention of vegetation or other natural features that mitigate natural hazard risk;
  - v. timing, location, scale and nature of **earthworks**;
  - vi. **earthworks** method;
  - vii. potential for the proposal to exacerbate natural hazard risk;
  - viii. benefits of infrastructure and performance of **critical infrastructure** following a natural hazard event; and
  - ix. mitigation of effects as they impact slope instability hazards.
- b. Restricted discretionary activities RD1 to RD49 will be assessed against the following criteria:
  - i. Whether the proposal and associated **hazard mitigation works**:
    - A. can be shown, based on evaluation by a Chartered Professional Engineer with experience in geotechnical engineering, using best practice methods, to increase the stability of land and/or protect structures and **buildings** and their occupants;
    - B. can be shown, based on evaluation by a Chartered Professional Engineer with experience in geotechnical engineering, using best practice methods, to achieve an acceptable risk to life or property, including the extent to which an **Annual Individual Fatality Risk** of  $10^{-4}$  (1 in 10,000) or better can be achieved; and

- C. will have appropriate monitoring procedures applied, with inspections and maintenance undertaken and reported to the Council.
- ii. Whether, due to the sensitive nature of the proposed activity (for example, childcare centre, playground, hospital), an Annual Individual Fatality Risk lower than  $10^{-4}$  is appropriate.
- iii. Whether development of the site transfers risk to another site.
- iv. Whether the location and design of proposed building platforms, access, earthworks, retaining walls and services to the site are the most appropriate considering the risk of natural hazards on the site.
- v. Provision for ground-strengthening, foundation design, protection structures and the ability of these to be incorporated into the subdivision consent as conditions or consent notices.
- vi. The extent that surface or subsurface drainage patterns and stormwater management are impacted as a result of hazard mitigation works, and whether these have an effect on the site or surrounding sites.
- vii. Where critical infrastructure is involved, whether the infrastructure is designed in a way to continue to operate safely in the event of a significant natural hazard occurring, including containment of any hazardous substances associated with that infrastructure.
- viii. For infrastructure generally, the extent of benefits associated with that infrastructure, whether there is a functional or operational requirement for that location and whether there are any practical alternatives.
- ix. Whether or not the work would be carried out under the supervision of either a Chartered Professional Engineer with experience in geotechnical engineering or a Professional Engineering Geologist (IPENZ registered).
- x. For RD 34, RD 36, RD 37, RD 38, RD 39 and RD 40 only, where the use and storage of hazardous substances are involved, whether the facility is designed in a way to manage the residual risks of adverse effects from hazardous substances to acceptable levels in the event of a significant natural hazard event occurring.

## 5.7 General procedures — information requirements

### 5.7.1 Additional information requirements for resource consent applications in the Liquefaction Management Area where a geotechnical report is required

Liquefaction potential

- a. Applicants will be required to supply the results of a detailed geotechnical investigation and interpretation. The level of investigation should correspond with the scale and significance of the liquefaction hazard. Plans and information shall:
  - i. identify any areas which require particular ground strengthening or other mitigation measures, and recommendations for such mitigation;
  - ii. identify any areas which should be excluded from built development, due to geotechnical constraints, or which require geotechnical setbacks, including areas near the edges of rivers, streams, lakes, wetlands, stormwater detention areas and swales where lateral spread is likely to occur; and
  - iii. indicate any options and recommended locations for the proposed land use, transport features and other infrastructure recommended by the geotechnical engineer.
- b. All geotechnical reports in respect of liquefaction potential are to be prepared by a Chartered Professional Engineer with experience in geotechnical engineering or a Professional Engineering Geologist (IPENZ registered), and should contain all relevant geotechnical information, presented in both a factual and interpretive manner.

### 5.7.2 Additional information requirements for resource consent applications within Slope Instability Management Areas

- a. Plans and accompanying information shall show:
  - i. the geological and geotechnical constraints across the site, including any relationship to or effect on areas of actual or potential instability of the site, including the location of any inferred faults.
  - ii. the location of the site in relation to the natural hazard, or the location of the hazard on the site itself, and the location of building platforms in relation to the hazard.
  - iii. the nature of the proposed activities on the site and the impact on other sites potentially affected by the natural hazard, and the effect of the hazard on the activity and vice versa.
- b. All geotechnical reports are to be prepared by a Chartered Professional Engineer with experience in geotechnical engineering or a Professional Engineering Geologist (IPENZ registered), and should contain all relevant geotechnical information, presented in both a factual and interpretive manner. The design of rockfall protection structures must be carried out by a Chartered Professional Engineer with specific experience in the investigation, design and/or construction of rockfall protection structures, who has registered with the Council.

### 5.7.3 Additional information requirements for all resource consent applications for subdivision


#### 5.7.3.1 Liquefaction Management Area

Liquefaction potential

- a. At subdivision consent application stage, detailed liquefaction susceptibility assessment and reporting will be required in accordance with the densities, depth, methods and reporting specified in *Ministry of Business, Innovation and Employment (December 2012): Part D of "Guidance: Repairing and rebuilding houses affected by the Canterbury Earthquakes": Guidelines for the geotechnical investigation and assessment of subdivisions in the Canterbury region: Minimum requirements for geotechnical assessment for land development ('flatland areas' of the Canterbury region)*.
- b. Subdivision consent applications will be required to include sufficient information and proposed measures to satisfy the Council that liquefaction risk (if present) can be adequately avoided, remedied or mitigated, including the potential effects of lateral spread within 200 metres of the edges of rivers, streams, lakes, wetlands, stormwater detention areas, swales or other areas with a sharp change in ground elevation.
- c. Subdivision plans shall show:
  - i. any areas which require particular ground strengthening or other mitigation measures, and recommendations for such mitigation;
  - ii. any areas which should be excluded from built development due to geotechnical constraints, or which require geotechnical setbacks; and
  - iii. any features of subdivision layout recommended by the geotechnical engineer, for example any recommended locations for proposed land uses, transport features and other infrastructure as a result of geotechnical constraints.
- d. All geotechnical reports with respect to liquefaction potential are to be prepared by a Chartered Professional Engineer with experience in geotechnical engineering, or a Professional Engineering Geologist (IPENZ registered), and should contain all relevant geotechnical information, presented in both a factual and interpretive manner.

# 5.8 Appendices

## Appendix 5.8.1 Gradient for excavation near stopbank for Rule 5.4.3.5.a. ii



Capital Delivery Team  
Capital Programmes Group  
Christchurch City Council

Msp: gg101583.dgn  
Date: 25/11/2014

**Appendix 5.8.2 Residential Unit Overlay within the High Flood Hazard Management Area for Rule 5.4.6.2 RD2**

